Project:	AIA#
Item:	
Location:	SIS#
Approved:	

SIDE MOUNT UNDERCOUNTER DRAWER REFRIGERATOR

UCRD67AHC Solid Door Refrigerator With Drawers Hydrocarbon Series MODEL: UCRD67AHC-2



5 Year Parts/Labor Warranty Available 7 Year Compressor Warranty

CABINET CONSTRUCTION

- Stainless steel front, sides, top, door, drawers and grille (galvanized steel back & bottom)
- Interior liner is made of corrosion resistant aluminum
- Full electronic control
- Undercounter feature a 1/2" thick sub-top
- Interior thermometer is standard
- Self-closing door with 120° stay-open feature, on lift-off hinges
- Magnetic gasket attached to each door for positive seal
- Two (2) epoxy-coated steel wire shelves
- Field-reversible door
- Snap-in drawer gaskets
- Upper and lower pull-out drawers accommodate 6" deep pans
- Stainless steel drawer frames supported on telescoping drawer slides
- Drawer slides include locking mechanism that prevents drawer from being inadvertently pulled off cabinet
- 6" Casters, (2) with brakes standard

OPTIONS & ACCESSORIES

- 3 Year parts/labor standard, additional 2 year warranty available
- Stainless steel back
- Stainless steel interior
- 16 Gauge stainless steel top
- · Additional shelves
- Shelf clips
- Right or left hinged door
- Lock (doors only)
- · Wire shelf divider
- 3" Casters
- 6" Legs (stainless steel, black or seismic/flange)
- Low profile casters
- Roller kit
- Remote option* (see note on back on page)

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Adaptive defrost
- Epoxy coated evaporator coil
- Refrigerators capable of maintaining product temperature between 36°F and 38°F






3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com




MODEL	UCRD67AHC-2	
EXTERNAL DIMENSIONAL DATA		
Width Overall	67"	
Depth Overall with Handle & Bumper	34 ¾"	
Height Overall with 6" Casters	34 ½"	
Number of Drawers	2	
Drawer Openings	(2) 21 %" x 10 %"	
Depth with Drawer Extended	57 ½"	
Number of Doors	1	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	19.2	
Internal Width Overall (in)	63"	
Internal Depth Overall (in)	26"	
Internal Height Overall (in)	25"	
Number of Shelves	2	
ELECTRICAL DATA		
Full Load Amperes	2.0	
REFRIGERATION DATA		
Horsepower	1/5	
Capacity (BTU/Hr)	1350	
Heat Rejection (BTU/Hr)	2025	
Charge (lbs/grams/ounces)	0.243 / 110 / 3.89	
SHIPPING DATA		
Gross Weight - Crated	395 lbs	
Height - Crated	48"	
Width - Crated	70"	
Depth - Crated	37"	

*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.



Undercounter Door/Drawer Refrigerator - Side Mount Model: UCRD67AHC-2





ELECTRICAL CONNECTION



Unit pre-wired at factory and include 8' long cord and plug set.

