


Project:	AIA#
Item:	
Location:	SIS#
Approved:	

## REMOTE BLAST CHILLER

BF202AP Solid Door Roll-In Blast Chiller

MODEL: BF202AP-1P





#### **CABINET CONSTRUCTION**

- · Stainless steel exterior and interior
- · Die-formed interior floor has rounded corners
- · Central drain for easy cleaning
- Anti-condensation perimeter heating around door opening
- · Ergonomic door handle and stainless steel
- Snap in place magnetic gaskets self closing door with hold open stop at 100°
- · Soft and hard, timed or core probe blast chilling
- · Soft and hard, timed or core probe shock freezing
- · Automatic recognition of core probe
- Multi point sensor temperature display button
- · Core probe heater button
- HACCP alarm display button
- · Pre-cooling cycle button
- Adjustable evaporator fan speed button
- Timed manual defrost button
- · USB data recorder
- Infinity mode program with adjustable set point
- · Automatic conservation mode at end of cycle
- On board recipe book with 68 pre-set programs
- 99 Free memory positions for custom programs
- · LCD illuminated temperature display
- · Real time clock
- One, high precision heated multi sensor probe
- Maximum interior dimensions for carts: 30"W x 41"D x 75"H (not included)

#### **OPTIONS & ACCESSORIES**

- UV sterilization lamp (must be added at time of order)
- Single sensor probes (up to 4 possible)
- Change door swing
- Rs 485 connection for external monitoring system
- · Ramp (not included)

### **REFRIGERATION SYSTEM**

- Remote refrigeration system uses R404 refrigerant (condensing unit to be provided by others)
- Evaporator fitted with a high flow rate fan insures maximum cooling efficiency
- · Indirect air flow assures highest product quality
- · Manual defrosting with door open on a timed cycle
- Blast chilling (194°F to 37°F in 90 minutes) or shock freezing (194°F to 0°F in 240 minutes) cycles











3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com



MODEL	BF202AP-1P	
EXTERNAL DIMENSIONAL DATA		
Width Overall (in)	59.06"	
Depth Overall (in)	54.13"	
Height Overall (in)	87.80"	
Number of Doors	1	
Width, Door Opening (in)	85.83"	
PERFORMANCE DATA		
Sheet Pan Capacity* (18" x 26")	20	
Steam Table Pan Capacity* (12" x 20")	40	
Chilling Capacity In 90 Min	465 lbs	
Freezing Capacity In 240 Min	310 lbs	
Climate Class	5	
Capacity Mobile Cart(s)	1 GN 2/1	
ELECTRICAL DATA		
Cabinet Voltage	208-240/60/3	
Total Amperes	9.0	
NEMA Plug	N.A.	
REFRIGERATION DATA		
Condensing Unit Size, HP	N.A.	
Refrigerant	R404	
Capacity (BTU/Hr) (113°F/-13°F)	46,736	
Heat Rejection (W) (14°F/95°F)	N.A.	
Refrigerant Amount (lbs)	N.A.	
WEIGHT DATA		
Gross Weight - Crated	1044 lbs	
Height - Crated	89"	
Width - Crated	55"	
Depth - Crated	70"	

\*Note - Pans not included

# Remote Blast Chiller/Shock Roll-In Freezer

