

PROJECT:		
ITEM #		QTY:
MODEL #		
AIA #	SIS #	

# **VICTORY ELITE™ TOP MOUNT REFRIGERATOR**

## **VERSA-3D-HG-HC**



### **EXCLUSIVE WARRANTY**

- 6 Year Parts & Labor Warranty
- 7 Year Compressor Warranty
- ► Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)



#### **CABINET CONSTRUCTION**

- · Stainless Steel Front, Gray Coated Sides
- · Aluminum Interior
- Snap-In, Magnetic Door Gasket(s)
- · Heavy Duty Cam Lift Hinges
- · Stay-Open Door Feature For Easy Product Loading
- · Required Clearance Is 12" Top, 3" Rear And 0" Sides
- 6" Casters
- 8' Cord And Plug

#### **FEATURES**

- High Performance Refrigeration System With An Electronic Control
- · Expansion Valve Technology
- · Energy Efficient LED Lighting
- 9 Heavy Duty Epoxy Coated Shelves

#### REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- · Hot Gas Condensate Evaporator
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- · Epoxy Coated Evaporator Coil, Located Out Of The Food Zone
- Refrigerator Capable Of Maintaining Product Temperature Between 36°F And 38°F



#### **OPTIONS & ACCESSORIES**

- · Stainless Steel Back
- · Stainless Steel Breaker Caps
- Stainless Steel ExteriorStainless Steel Interior
- Tray Slides
- 3" Casters Or 6" Legs (no charge at time of order)
- · Seismic/Flanged Legs
- Additional Shelves: Heavy Duty Epoxy Coated Chrome Plated Or Stainless Steel

Please Verify Qualifying Units By Visiting: www.energystar.gov/cfs

Remote Models\* (6" legs only)
(refrigerant must be specified at time of order, see
note)

3779 Champion Blvd, Winston-Salem, NC 27105

ph: (888) 845-9800 fax: (800) 253-5168


Sales@VictoryRefrigeration.com VictoryRefrigeration.com


Rev. 9/28/23 Printed in U.S.A.


APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_



# **VERSA-3D-HG-HC**







We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements,  $additions\ or\ replacements\ for\ previously\ purchased\ equipment.\ Dimensional\ tolerances\ +/-\ 1/4".\ Metric\ dimensions\ (MM)$ 

#### 12" Top and 3" rear clearance is required

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS	
Net Capacity (cubic ft.)	71.52	Cabinet Voltage**	115/60/1	Height	88"
Width, Overall (in.)	78"	Total Amperes	6.0	Width	80"
Depth, Overall (with handles)	33 5/8"	NEMA Plug (8' cord)	5-15P	Depth	36"
Height Overall (6" casters)	84 3/4"	REFRIGERATION DATA		Crated Weight	720 lbs
Depth, Door Open 90°	55 1/8"	Condensing Unit Size, HP	1/3	*NOTE: Remote units are field wired and comes with 6" legs. Refrigerant must be specified	
Door Opening (in.)	215/8" x 29 5/8"	Refrigerant	R290		
No. Of Doors/Shelves	6/9	Capacity (BTU/HR) (100°F/20°F)	2800		
		Heat Rejection (BTU/HR)	4200	at time of order.	
		Charge (lbs/grams)	0.3307/150		

<sup>\*\*</sup> NOTE: This unit utilizes variable speed compressor technology. The compressor can experience nuisance tripping on Class A GFCI outlets which have a trip limit of 4 mA to 6 mA. To avoid this issue in a location that requires GFCI circuit protection, Victory recommends using a HUBBELL Model Number GFRST83W 20A Heavy Duty Hospital Grade Self-Test GFCI Receptacle.

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Rev. 9/28/23 Printed in U.S.A.

