

PROJECT:			_
ITEM #		QTY:	
MODEL #			
			_
AIA #	SIS #		

WORKTOP REFRIGERATOR WITH DRAWERS

VWRD36HC-2

EXCLUSIVE WARRANTY

- 7 Year Parts, Labor and Compressor
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)





CABINET CONSTRUCTION

- · Stainless Steel Exterior (galvanized back & bottom)
- · Aluminum Interior
- · Stainless Steel 20 Gauge Drawers
- · 4" High, Foamed-In-Place Backsplash
- One Piece, Snap-In Magnetic Drawer Gaskets
- · 6" Casters Two With Brakes
- · 8' Cord And Plug (see electrical data for details)

FEATURES

- · Full Electronic Control
- · Stay-Open Drawer Feature For Easy Product Loading
- · Low Profile Horizontal Drawer Handles
- · Heavy-Duty Pan Supports Provided
- Drawers Accommodates 6" Deep Full Size Food Service Pans In Both Upper And Lower Drawers (pans not included)
- · Telescoping Drawer Slides With Locking Mechanism

REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- Rear Mounted Refrigeration System
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- **Epoxy Coated Evaporator Coil**
- Refrigerator Capable Of Maintaining Product Temperature 36°F To 38°F



Please Verify Qualifying Units By Visiting: www.energystar.gov/cfs

OPTIONS & ACCESSORIES

- · Stainless Steel Interior
- · Stainless Steel Back

· Cutting Board

- · Drawer Locks
- · 6" Leas Or 6" Seismic Leas
- · Casters: 3", Roller Kit, Low Profile
- Remote Models* (6" legs only) (refrigerant must be specified at time of order, see note on back on page)

3779 Champion Blvd, Winston-Salem, NC 27105


ph: (888) 845-9800 fax: (800) 253-5168


Rev. 7/18/24 Printed in U.S.A APPROVAL: _ DATE: _





VWRD36HC-2











We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

3" Bottom & 2" Rear clearance is required

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS		
Net Capacity (cubic ft.)	8.5	Cabinet Voltage	115/60/1	Height	48"	
Width, Overall (in.)	36"	Total Amperes	2.0	Width	38"	
Depth, Overall (with handle)	32 3/4"	NEMA Plug (8' cord)	5-15P	Depth	38"	
Height Overall (6" casters)	39 5/8"	REFRIGERATION DATA		Crated Weight	276 lbs	
Depth, Drawer Extended	48 3/4"	Condensing Unit Size, HP	1/6			
Drawer Openings (in.)	31 3/4" × 7 5/8" 31 3/4" × 11 1/2"	Refrigerant*	R-290	*NOTE: Remote units are field wired and comes with 6" legs. Refrigerant must be specified		
No. Of Drawers	2	Capacity (BTU/HR) (100°F/20°F)	1094			
		Heat Rejection (BTU/HR)	1641	at time of order.		
		Charge (lbs/grams/ounces)	0.243 / 110 / 3.89			

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168 Sales@VictoryRefrigeration.com VictoryRefrigeration.com

Rev. 7/18/24 Printed in U.S.A.

