

PROJECT: _	
ITEM #	
MODEL #	

AIA #

QTY: _

EXTRA WIDE PASS-THRU SOLID DOOR FREEZER

FSA-2D-S1-EW-PT-HC



EXCLUSIVE WARRANTY

- **6 Year Parts & Labor Warranty**
- 7 Year Compressor Warranty
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)





OPTIONS & ACCESSORIES

- Secure-Temp[™] Technology
- Stainless Steel Case Back
- Stainless Steel Kick Plate
- Exterior Door Laminate
- Door Swing Orientation (at time of order)
- Additional Shelves
- Heat Shield (left, right)
- Tray Slides (type A & A/C)

• 3", 6" Casters Or 6" Seismic Legs

• FlexTemp Models Maintain Between 0°F And 20°F

Environmental Concerns Hot Gas Condensate Evaporator

Refrigeration System Uses R-290 Refrigerant To Comply With All

- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- Epoxy Coated Evaporator Coil, Located Out Of The Food Zone
- Freezer Capable Of Maintaining Product Temperature -10°F



Please Verify Qualifying Units By Visiting: www.energystar.gov/cfs

- · Correctional Package
- Remote Models* (6" legs only) (refrigerant must be specified at time of order, see note)

3779 Champion Blvd, Winston-Salem, NC 27105 ph: (888) 845-9800 fax: (800) 253-5168

Sales@VictoryRefrigeration.com VictoryRefrigeration.com

APPROVAL: _____







· One Piece, Snap-In Magnetic Door Gaskets

• 6" High Adjustable Stainless Steel Legs 8' Cord And Plug (see electrical data for details)

Full Electronic Control With Touchpoint Interface

Stay-Open Door Feature For Easy Product Loading

Magnetic Door Switch Automatically Activates Interior LED Light

CABINET CONSTRUCTION

• 20 Gauge Stainless Steel Door

Low Profile Vertical Door Handles

 Energy Saving Thermal Breaker Stainless Steel Breaker Caps 6 Silver Freeze Wire Shelves

 Expansion Valve Technology Manager's Lockout Feature Anti-Condensate Perimeter Heater Variable Speed Compressor Technology

REFRIGERATION

 Heavy-Duty Cylinder Locks Stainless Steel Interior Door Liner

Hinged Front Shroud

FEATURES


Stainless Steel Exterior


Aluminum Interior


SIS #



foren







We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

12" Top and 3" rear clearance is required

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS	
Net Capacity (cubic ft.)	52.97	Cabinet Voltage**	115/60/1	Height	88″
Width, Overall (in.)	58 3/8″	Total Amperes	13.9	Width	66″
Depth, Overall (with handle)	38 3/4"	NEMA Plug (8' cord)	5-20P	Depth	48″
Height Overall (6" legs)	84 1/8″	REFRIGERATION DATA		Crated Weight	662 lbs
Depth, Door Open 90°	87 1/8″	Condensing Unit Size, HP	(2) 3/4	*NOTE: Remote units are field wired and comes with 6" legs. Refrigerant must be specified at	
Door Openings (in.)	23" x 54 5/8"	Refrigerant	R-290		
No. Of Doors/Shelves	4/6	Capacity (BTU/HR) (100°F/-20°F)	4900		
		Heat Rejection (BTU/HR)	7350	time of order.	
		Charge (Ibs/grams)	0.2866/130		

** NOTE: This unit utilizes variable speed compressor technology. The compressor can experience nuisance tripping on Class A GFCI outlets which have a trip limit of 4 mA to 6 mA. To avoid this issue in a location that requires GFCI circuit protection, Victory recommends using a HUBBELL Model Number GFRST83W 20A Heavy Duty Hospital Grade Self-Test GFCI Receptacle.

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com VictoryRefrigeration.com

Rev. 9/1/23 Printed in U.S.A.

an Ali Group Company

