


# REGULAR PLATE DISPENSERS: CABINETS

*Non-Heated or Heated, Lakeside's award-winning plate dispensers are just what you need to easily transport and distribute plates.*

- Adjusting height level is easy and convenient. Simply detach and attach springs as needed with no tools required
- Easy glide design is non-stick for smooth, accident-free operation
- All 4" swivel casters, 2 with brake, allow easy maneuverability.
- All welded construction increases durability

- Stainless steel material is easy to clean and sanitize
- Corner bumpers protect walls and furniture
- Dispensers have 25" (635) stacking height capacity
- On Heated Models, each dispenser features its own thermostatic control to manage and adjust temperature

 Freight Class: **92.5**  
Ships in: **4** days or less!

## NON-HEATED | STAINLESS STEEL



Model	Accommodates Plate Sizes	Overall Size				Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m <sup>3</sup> )
		W	L	H	(W L H)		
<b>1 Stack - Non-Heated</b>							
5100	Up to 5" (Up to 127)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	74 (33.3)	17.5 (.48)
5105	5-1/8" to 5-3/4" (130 to 146)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	74 (33.3)	17.5 (.48)
5106	5-7/8" to 6-1/2" (149 to 165)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	76 (34.2)	17.5 (.48)
5107	6-5/8" to 7-1/4" (168 to 184)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	79 (35.6)	17.5 (.48)
5108	7-3/8" to 8-1/8" (187 to 206)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	85 (38.3)	17.5 (.48)
5109	8-1/4" to 9-1/8" (210 to 232)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	87 (39.2)	17.5 (.48)
5110	9-1/4" to 10-1/8" (235 to 257)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	89 (40.1)	17.5 (.48)
5111	10-1/4" to 11" (260 to 279)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	90 (40.8)	17.5 (.48)
5112	11-1/4" to 12-1/4" (286 to 311)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	93 (41.9)	17.5 (.48)
<b>2 Stack - Non-Heated</b>							
5200	Up to 5" (Up to 127)	18-1/2"	32"	39-7/8"	(470 813 1013)	83 (37.7)	19.5 (.54)
5205	5-1/8" to 5-3/4" (130 to 146)	18-1/2"	32"	39-7/8"	(470 813 1013)	83 (37.7)	19.5 (.54)
5206	5-7/8" to 6-1/2" (149 to 165)	18-1/2"	32"	39-7/8"	(470 813 1013)	85 (38.6)	19.5 (.54)
5207	6-5/8" to 7-1/4" (168 to 184)	18-1/2"	32"	39-7/8"	(470 813 1013)	87 (39.5)	19.5 (.54)
5208	7-3/8" to 8-1/8" (187 to 206)	18-1/2"	32"	39-7/8"	(470 813 1013)	94 (42.6)	19.5 (.54)
5209	8-1/4" to 9-1/8" (210 to 232)	18-1/2"	32"	39-7/8"	(470 813 1013)	96 (43.6)	19.5 (.54)
5210	9-1/4" to 10-1/8" (235 to 257)	18-1/2"	32"	39-7/8"	(470 813 1013)	98 (44.5)	19.5 (.54)
5211	10-1/4" to 11" (260 to 279)	20-3/4"	36-1/2"	39-7/8"	(527 927 1013)	105 (47.6)	24.4 (.67)
5212	11-1/4" to 12-1/4" (286 to 311)	20-3/4"	36-1/2"	39-7/8"	(527 927 1013)	110 (49.8)	24.4 (.67)
<b>3 Stack - Non-Heated</b>							
5300	Up to 5" (Up to 127)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	149 (67.7)	28.0 (.77)
5305	5-1/8" to 5-3/4" (130 to 146)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	149 (67.7)	28.0 (.77)
5306	5-7/8" to 6-1/2" (149 to 165)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	152 (69.1)	28.0 (.77)
5307	6-5/8" to 7-1/4" (168 to 184)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	180 (81.8)	28.0 (.77)
5308	7-3/8" to 8-1/8" (187 to 206)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	192 (87.3)	28.0 (.77)
5309	8-1/4" to 9-1/8" (210 to 232)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	196 (89.1)	28.0 (.77)
5310	9-1/4" to 10-1/8" (235 to 257)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	200 (90.9)	28.0 (.77)
<b>4 Stack - Non-Heated</b>							
5400	Up to 5" (Up to 127)	32"	32"	39-7/8"	(813 813 1013)	176 (80.0)	33.0 (.91)
5405	5-1/8" to 5-3/4" (130 to 146)	32"	32"	39-7/8"	(813 813 1013)	176 (80.0)	33.0 (.91)
5406	5-7/8" to 6-1/2" (149 to 165)	32"	32"	39-7/8"	(813 813 1013)	177 (80.5)	33.0 (.91)
5407	6-5/8" to 7-1/4" (168 to 184)	32"	32"	39-7/8"	(813 813 1013)	177 (80.5)	33.0 (.91)
5408	7-3/8" to 8-1/8" (187 to 206)	32"	32"	39-7/8"	(813 813 1013)	178 (80.9)	33.0 (.91)
5409	8-1/4" to 9-1/8" (210 to 232)	32"	32"	39-7/8"	(813 813 1013)	183 (83.2)	33.0 (.91)
5410	9-1/4" to 10-1/8" (235 to 257)	32"	32"	39-7/8"	(813 813 1013)	184 (83.6)	33.0 (.91)

Measurements in ( ) denote metric millimeters, unless otherwise specified. Lake-Glide® Casters: 4" (102) - All swivel, 2 ea. w/brake, extra-load.