




BLS-4HTD-2



TOUCH digital programmable controls:



- 9 BAKING STEPS
- 0 - inf TIMER
- 120° - 500° F TEMPERATURE
- 0-20-40-60-80-100% HUMIDITY
- 2 FAN SPEEDS
- PROOFER CONTROL
- 99 PROGRAMS
- WI-FI
- DATA DRIVEN COOKING - CHAIN BASED APPLICATION



Heavy-Duty Stand w/ Casters for half size ovens

- Holds 5 half size sheet pans (not included)
- Aluminum



Made to Cadco specifications by UNOX S.p.A., Italy NSF, MET to UL & CSA Standards
Cadco Model XAFT-03HS-LD = UNOX Model XAFT-03HS-ELDUS

We recommend that the end user have a standard ice-machine filter when using a humidity hookup.

Bakerlux Station Includes:



Model	Color	Volts	Watts	AMPS	Unit Dimensions
XAFT-04HS-TD	Stainless	208/240	3800	16	W: 23 5/8" H: 19 5/8" D: 29"
OST-034A-CS	Stainless	N/A	N/A	N/A	W: 23.87" H: 21.5" D: 27"

Shipping Unit Dimensions

Skid 1: 150 lbs 48 L x 40 W x 30H
Skid 2: 200lbs 48 L x 40 W x 50 H