

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

UUC48F 48" Undercounter Work Top Freezer - 12 Cu. Ft.



FEATURES

- ▶ Stainless steel exterior and interior
- ▶ Refrigeration system keeps food at safe temperatures
- ▶ Self-closing doors with 90 degree stay-open feature
- ▶ Adjustable heavy-duty PVC coated shelves
- ▶ Recessed door handle
- ▶ Electronic control system
- ▶ Preinstalled heavy-duty casters with brakes
- ▶ Removable installation board
- ▶ Hydro-Carbon R290 refrigerant
- ▶ 4" **backsplash optional**

This Coldline commercial undercounter freezer is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
 - ETL Sanitation Listed
- Conforms to UL & NSF Standards



US Restaurant Group is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.



Datasheet

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	47.2"W x 29.5"D x 35.5"H
Low Profile Dimensions	47.2"W x 29.5"D x 34"H
Interior Dimensions	42.5"W x 22.9"D x 23.5"H
Packaging Dimensions	50"W x 32.3"D x 38.5"H
Working Height	35.3"
Net Volume	12 cu. ft.
Unit Weight	214 lb.
Shipping Weight	275 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	4.5
Plug Type	NEMA 5-15P
Power Cord Length	84"

COOLING

Temperature Range	-8°F to 0°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/4+

CONSTRUCTION

Exterior Material	Stainless Steel
Interior Material	Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	(2) Qty: 20.8"W x 17.1"D
Shelf Load Capacity	90 lb.
Shelf Material	Epoxy Coated Steel
Adjustable Shelf	Yes
Interior Light	No
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

DIAGRAM

MODEL:UUC48F

MFR MODEL:UUC-48F-HC



NEMA 5-15P

