

Job:			
14 NI -			
Item No.			

## **Stainless Steel Breakfast Cart**

## **Models**

BST-46 EBC


Heavy Duty Mobile Breakfast Cart designed to meet the demands of school nutrition programs and commercial food service operations


- Designed specifically for school nutrition programs
- Stainless steel interior and exterior
- Two 12"X 20" removable ice pans for cool or ambient service and display
- Slanted overshelf for grab and go items
- Two full-sized end shelves are easily removable without tools
- Spacious undercounter storage area
- Heavy-duty 5" locking casters for superior mobility






MODEL#	WIDTH DIM A	DEPTH DIM B	HEIGHT DIM C	SHIP WEIGHT
BST-46 EBC	76"	30"	34"	250 Lbs.







**GENERAL**: Stainless steel breakfast cart shall be constructed with 16 gauge stainless steel base, caster channels, and top supports; 18 gauge stainless steel back and side panels. All exterior surfaces shall be ground and polished to a #4 finish.

**TOP**: Top shall be one piece, 18 gauge stainless steel. Top shall be cross-braced for rigidity, with two cut-outs for 12"X 20" full sized steam pans. Includes two full-sized 6" deep steam pans (removable).

**END SHELVES**: End shelves shall be 27"X 14" and constructed from 18 gauge stainless steel. Shelf shall be easy to remove without tools. Shelf easily attaches to breakfast cart body using proprietary "Z" clip system.

**SLANTED OVERSHELF**: Overshelf shall be 48"X 23" with 11%" upturn and flanges. Overshelf shall be constructed from 18 gauge stainless steel and slanted at 20 degrees from counter surface. Tubular shelf supports shall be 15%" outer diameter with 16 gauge wall.

**CASTERS**: Unit shall have 4 heavy duty 5" casters, two locking, through-bolted to the 16 gauge hat-channels.

**LISTINGS: NSF** 

**OPTIONAL MAGNETIC GRAPHICS**: Multiple merchandising graphics available as an additional option. Ships separate from unit.





451 E. County Line Rd. • P.O. Box 1089 • Mooresville, IN 46158 800-733-8073 • Local 317-831-7030 • Fax 317-831-7036 www.secoselect.com