

Vacuum Packaging System Spec Sheet

GREENVAC VACUUM PACKAGING SYSTEM		FEATURES
ITEM: GV150-GN1/3		GN1/3 are manufactured with 17/18 gauge chrome nickel steel. In comparison, conventional containers are manufactured with 22/24 gauge steel. Oven safe.
		LIDS
DESCRIPTION		Developed from a high performance plastic (Tritan) Product Facts: •High impact resistance •High weather resistance •High chemical resistance •Perfect abrasions-resistance and sliding condition •Minimum water absorption very high dimensions stability •Minimum specific weight •Excellent high impact resistance •High barrier-character •Lids short term resistant to temperatures up to 194°F (dishwater)
The robust, stainless steel 150-1/3 GN vacuum packaging system is standard equipped with a vacuum lid, gasket seal & nozzle. NSF certified		SEALS
WARRANTY		The gaskets are made of food compatible silicone. The valve is produced from latex. All GreenVAC components are new developments for a use in high vacuum. The atmospheric pressure in such a vacuum has a value of 900 - 1700kg / cm2 depending on the size of GreenVAC container!
All models shown come with Invacus standard one year warranty against defects in materials and workmanship. For full warranty details, please refer to: Invacus.com		Used in connection with: •Henkelman Vacuum Machine w/External Adapter. •A retrofitted chamber machine. •Directly in the chamber of a standard vacuum machine, sizes are dependent on the chamber size.
 		
GREENVAC		
 www.invacus.com	Invacus LLC - info@invacus.com / 331-979-2013 493. W. Fullerton Ave, Elmhurst, IL 60126	

DIMENSIONS IN INCHES



 www.invacus.com	Invacus LLC - info@invacus.com / 331-979-2013 493. W. Fullerton Ave, Elmhurst, IL 60126
--	---