

| Project:  | AIA# |
|-----------|------|
| ltem:     |      |
| Location: | SIS# |
| Approved: |      |

MODEL:

**PFD1HC-1AHS** 

# P SERIES TOP MOUNT PASS-THRU FREEZER

# PFD1HC Half-Solid Door Pass-Thru Hydrocarbon Series



## **OPTIONS & ACCESSORIES**

- 3 Year parts/labor standard, additional 2 year warranty available
- Stainless steel interior
- Additional shelves
- Shelf clips
- 3" or 6" Casters
- 6" Seismic legs
- Tray slides (type A & A/C)
- Door swing orientation (at time of order)
- Remote option\* (see note back on page)

#### 5 Year Parts/Labor Warranty Available 7 Year Compressor Warranty

#### **CABINET CONSTRUCTION**

- Exterior stainless steel front and side (galvanized top, bottom & back)
- · Interior is made of corrosion resistant aluminum
- Stainless steel door liner
- Full electronic control
- Expansion valve technology
- Self-closing doors with 120° stay-open feature
- 22 Gauge stainless steel pass-thru half door
- LED interior light
- Cylinder locks
- Snap-in magnetic gaskets for positive door seal
- · Hinged front shroud
- Energy saving thermal breaker
- Stainless steel breaker caps
- Three (3) heavy-duty epoxy wire coated shelves
- 6" High adjustable stainless steel legs
- 8' Cord and plug (see electrical data for details)

## **REFRIGERATION SYSTEM**

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Adaptive defrost
- Epoxy coated evaporator coil, located out of the food zone
- Freezer capable of maintaining product temperature down to -10°F






3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com



| MODEL                        | PFD1HC-1AHS        |  |
|------------------------------|--------------------|--|
| EXTERNAL DIMENSIONAL DATA    |                    |  |
| Width Overall                | 26 ½"              |  |
| Depth Overall with Handles   | 38 ³∕s"            |  |
| Height Overall               | 84 ½"              |  |
| Number of Doors              | 4                  |  |
| Depth with Door Open 90°     | 83 1⁄8"            |  |
| Door Openings (in)           | 21 ½" x 25 ¼"      |  |
| INTERNAL DIMENSIONAL DATA    |                    |  |
| NET Capacity (cubic ft.)     | 22.9               |  |
| Internal Width Overall (in)  | 22 ½"              |  |
| Internal Depth Overall (in)  | 26"                |  |
| Internal Height Overall (in) | 56 ⁵⁄≋"            |  |
| No. of Shelves               | 3                  |  |
| ELECTRICAL DATA              |                    |  |
| Full Load Amperes 115/60/1** | 9.1                |  |
| REFRIGERATION DATA           |                    |  |
| Horsepower                   | 3/4                |  |
| Capacity (BTU/Hr)            | 2450               |  |
| Heat Rejection (BTU/Hr)      | 3675               |  |
| Charge (lbs/grams/ounces)    | 0.2866 / 130 / 4.6 |  |
| SHIPPING DATA                |                    |  |
| Gross Weight (crated lbs)    | 471 lbs            |  |
| Height - Crated              | 88"                |  |
| Width - Crated               | 35"                |  |
| Depth - Crated               | 45"                |  |

#### P Series Top Mount Freezer Pass-Thru Model: PFD1HC-1AHS



\*NOTE: Remote units are field wired and come with 6" legs.

Refrigerant must be specified at time of order.

#### ELECTRICAL CONNECTION



115/60/1\*\*Unit pre-wired at factoryNEMA 5-15Pand include 8' long cordand plug set.

\*\* NOTE: This unit utilizes variable speed compressor technology. The compressor can experience nuisance tripping on Class A GFCI outlets which have a trip limit of 4 mA to 6 mA. To avoid this issue in a location that requires GFCI circuit protection, Beverage-Air recommends using a HUBBELL Model Number GFRST83W 20A Heavy Duty Hospital Grade Self-Test GFCI Receptacle.



3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com

an Ali Group Company

