

Ware Washer Water Treatment



Scale Control Water Treatment for Ware Washers

High temperature scale control treatment eliminates:

- ☑ Ware washer break down maintenance
- ☑ Loss of production during break downs
- ☑ Scale formation on heating elements
- ☑ Use of harsh acids to dissolve scale
- ☑ Expensive service calls

Our ware washer water treatment systems are a safe, effective, and affordable way to maintain a scale free ware washer, providing continuous ware washer operation. Systems IV provides an easy to change cartridge that is changed approximately every 6 months.



Our ware washer water treatment uses Citryne which provides superior scale control with a proprietary water treatment technology proven to control scale problems in commercial ware washers. Our water treatment introduces a FDA approved special treatment blend at a constant rate to maximize scale elimination.



TERRY

(800) 557-3449 • www.terryh2o.com
6641 W. Frye Road • Chandler, AZ 85226



Ware Washer Scale Control

10" Hot Water Treatment for Glass Washers & Under Counter Ware Washers

Model: SC100HSYS (Complete system with housing, bracket, wrench and cartridge)

Replacement Cartridge: SC100H

Approx. Cartridge life: 25,000 gallons or 6 months
Maximum Temperature: 160°F (71.1°C)
Initial ΔP (psi)
Flow Rate (gpm): <1 psi @ 8 gpm (< 0.1 bar @ 30 L/min)
Maximum Pressure: 125 psi (8.62 bar)
Dimensions: 12-1/8" x 5-1/8" (308 mm x 130 mm)
3/4" inlet/outlet for easy installation



20" Hot Water Treatment for Door Type and Small Conveyor Ware washers

Model: SC200HSYS (Complete system with housing, bracket, wrench and cartridge)

Replacement Cartridge: SC200H

Approx. Cartridge life: 60,000 gallons or 6 months
Maximum Temperature: 130°F (71.1°C)
Initial ΔP (psi)
Flow Rate (gpm): <1 psi @ 8 gpm (< 0.1 bar @ 30 L/min)
Maximum Pressure: 125 psi (8.62 bar)
Dimensions: 22-1/4" x 5-1/8" (308 mm x 130 mm)
3/4" inlet/outlet for easy installation



20" Jumbo Hot Water Treatment for Medium & Large Conveyor Ware washers

Model: SC300HSYS (Complete system with housing, bracket, wrench and cartridge)

Replacement Cartridge: SC300H

Approx. Cartridge life: 95,000 gallons or 6 months
Maximum Temperature: 275°F (135°C)
Flow Rate (gpm): <1 psi @ 12 gpm (< 0.1 bar @ 30 L/min)
Maximum Pressure: 125 psi (8.62 bar)
Dimensions: 22-1/4" x 6-1/8"
3/4" inlet/outlet for easy installation



TERRY

6641 West Frye Road
Chandler, AZ 85226

800.557-3449 • FAX 480.961.1247 • www.terryh2o.com