



PRODUCT SPECIFICATION

Transportation Cart

Model #: HD-BTC72

UPDATED: November 2005

General Construction

Transport cart shall be a completely welded assembly. Casters shall be bolted to cart base caster plate mounts. Handle shall be connected to cart by inserting unit into handle bracket vertically; handle shall be removable. Handle can be secured into handle bracket with 5/16" x 2" pin. Handle shall be 38" high from floor to top. Handle shall have a push/pull safety handle which will be welded to the vertical handle. Safety handle shall protrude 6" out from vertical handle tubing. Cart shall be finished with an epoxy powder coating. The color shall be Black.

Capacities

12 rectangular tables (30"x72" or 36"x72") stacked horizontally.

12 seminar tables (18"x72" or 24"x72") stacked horizontally.

Dimensions

Overall dimensions shall be 81.0"L x 31.5"W x 38.0"H. These dimensions include the cart handle.

Transport cart base dimensions shall be 74.5"L x 31.5"W.

Cart base frame construction

Outside frame brace: 3/16" x 2" x 2" steel angle iron.

Lateral frame brace: 3/16" x 2" x 2" steel angle iron

End handle/swivel caster frame brace: 3/16" x 7/8" x 1 3/8" steel angle iron

Caster plate mounts: 6" x 6.5" x 8 gage caster mounts welded to lateral frame brace steel angle iron.

Handle tubing: 1.25" diameter, 16 gauge steel tubing

Handle brackets: 1 9/16", 10 gauge round steel tubing.

Standard Casters

Castors shall be weight rated to hold 650 pounds each / 2,600 pounds per cart. Standard casters shall be (4) 5" diameter x 2" width, phenolic composition material, axle roller bearings, and axle grease fittings attached. Fixed casters (2) - Each caster shall be affixed to caster mount plate by grade 8, 3/8" - 16 x 3/4" bolt with 3/8" locking nuts. Swivel casters (2) - Each caster shall be affixed to caster mount plate by grade 8, 3/8" - 16 x 3/4" bolt with 3/8"-16 lock nuts.

Warranty

Palmer Snyder warrants that all transportation carts will be new and manufactured with quality materials and workmanship. Palmer Snyder further agrees to replace promptly any part or parts which by reason of defective material or workmanship shall fail under normal use for a period of 5 years from date of acceptance. Warranty for rental companies is 1 year. All warranty issues are subject to management approval and are deemed prorated.