



1. Moving and Extraction by Electro-Mechanical Mechanism.
2. Does not Require Additional Molds for Extraction.
3. Reduced Maintenance Costs and Reduced Initial Investment.
4. Power Saving.
5. State of Art Semi-Hermetic Compressor.
6. Pump agitation.
7. Avoids Constant liquid exchanges.
8. Equipment with the best cost-benefit in the market.
9. Production control.
10. Digital Indication of Produced Units.
11. Wheels of Make Easy Deslocation.
12. Uses R404A Ecological Gas.
13. Production: 1800 up to 2400 Ice Pops / Hour – at 20°C
14. Works with 22 molds of 28 cavities of 63ml in the tank and 6 in the ramp.
15. Water-driven Condensation.
16. Automatic System for Mold Filling (Optional).



Model	Turbo 80
Electrical Installation	220 V, Threephase, 50 Hz / 60 Hz
Consumption of electricity	13 kW
Net Weight	725 kg (without propylene) 1040 kg (with propylene and forms)
Equipment Dimensions (WHL)	730 x 1320 x 3350 mm 28.74 x 51.97 x 131.89 in
Condensation	Water

**Technical Information may change without previous advice.*

***Production of the equipment depends on climatic conditions and locations where installation of the machine is located.*