

# KOLD-DRAFT

STILL THE ONLY CUBE OF ITS KIND.



### Plumbing:

- 3/4" FPT Potable Water Inlet
- 3/4" FPT Bin Drain
- 3/4" I.D. Flex Tubing Cuber Drain
- 3/8" FPT Condenser (Liquid-Cooled) Inlet
- 1/2" FPT Condenser (Liquid-Cooled) Outlet

### Exterior Finish:

300 Series Stainless Steel

### Refrigeration System:


Thermostatic Expansion Valve Controlled R290 Refrigerant

### Clearance Requirements:

Allow 4" Left Side, 8" Right Side and Back, and 6" Top for Ventilation and Utility Connections

### Condenser Heat Rejection:

BTUH/kW/Ton  
6,500/1.91/0.59 avg.  
8,750/2.6/0.729 peak



**Full Cube**  
1.25" x 1.25" x 1.25"

# X SERIES GTX560 - ICE MACHINE

## THE X-SERIES SIGNATURE

Produces up to 500lbs of ice per day. The X-Series from Kold-Draft features rounded corners, plastic top panels, plastic louvers and an LCD display. X-Series machines are stackable with other X-Series machines. Double the capacity in the same footprint.

### GTX560 Series Daily Capacities: Lbs of Ice per 24 Hours per Unit

Model Number	Electrical Volts/Hz/Ph	Condenser	Ice Capacity 24 Hours lbs (kg)		Energy Input 90°F (32°C) 70°F (21°C) kWh/100 lbs (kJ/kg)	Water Use gal/100lb (l/kg)		Min. Circuit Amp	Max. Fuse Size Amps
			70°F (21°C) 50°F (10°C) Ambient/Water	90°F (21°C) 70°F (10°C) Ambient/Water		90°F (32°C) / 70°F (21°C) Potable	Condenser		
<b>GTX561ACE</b>	115/60/1	Air	500 (227)	418 (190)	4.54 (360)	13.63 (1.1)	N/A	15.9	20
<b>GTX561LCE</b>	115/60/1	Liquid	459 (208)	426 (193)	4.17 (331)	12.96 (1.1)	133.77 (11.2)	15.1	20
<b>GTX564ACE</b>	208-230/60/1	Air	514 (233)	443 (201)	4.81 (382)	13.58 (1.1)	N/A	9.3	15
<b>GTX564LCE</b>	208-230/60/1	Liquid	459 (208)	426 (193)	4.17 (331)	12.96 (1.1)	133.77 (11.2)	8.7	15

### Dimensions/Weight

Description	Dimensions W x D x H	Ship Weight
Air Cooled	30.1" x 25.7" x 30.7" (76.5cm x 65.3cm x 78cm)	220lb (99.8kg)
Liquid Cooled	30.1" x 25.7" x 30.7" (76.5cm x 65.3cm x 78cm)	220lb (99.8kg)

### Recommended Operating Requirements

Description	Minimum	Maximum
Room Temperature	45°F (7°C)	110°F (43°C)
Water Temperature	45°F (7°C)	90°F (32°C)
Voltage 208-230	198V	253V
Voltage 115	104V	126V
Potable Water Pressure	20 PSIG (137 kPa)	100 PSIG (689 kPa)
Liquid-Cooled Condenser Pressure	20 PSIG (137 kPa)	100 PSIG (689 kPa)

### Compatible Storage Bins

Model Number	Dimensions W x D x H*	Capability	Ship Weight
<b>KDB230</b>	30.25" x 34" x 23" (76.8cm x 86.4cm x 58.4cm)	230lb (104kg)	112lb (51kg)
<b>KDB400</b>	30.25" x 34" x 37" (76.8cm x 86.4cm x 94cm)	400lb (181kg)	163lb (74kg)

\*Height includes 6" (15.2cm) legs

### Accessories

Model Number	Description	Ship Weight
<b>102149601</b>	GTX560 Series on top of GTX560 Stacking Kit	5lb (2.3kg)
<b>DR3-GT</b>	GT/GTX Series Drain Riser Kit, 3"	20lb (9kg)

KOLD-DRAFT recommends all ice machines have water filtration. Please reference water filtration specification sheet.



**KOLD-DRAFT**

101 Corporate Woods Parkway, Vernon Hills, IL 60061  
1-800-840-9577 | info@kold-draft.com | www.kold-draft.com



KD SS GTX560 01-26