

KOLD-DRAFT

STILL THE ONLY CUBE OF ITS KIND.



Plumbing:

3/4" FPT Potable Water Inlet
3/4" FPT Bin Drain
3/4" I.D. Flex Tubing Cuber Drain
3/8" FPT Condenser (Liquid-Cooled) Inlet
1/2" FPT Condenser (Liquid-Cooled) Outlet

Exterior Finish:

300 Series Stainless Steel

Refrigeration System:

Thermostatic Expansion Valve Controlled
R290 Refrigerant

Clearance Requirements:

Allow 4" Left Side, 8" Right Side and Back,
and 6" Top for Ventilation and Utility
Connections

Condenser Heat Rejection:

BTUH/kW/Ton
13,850/4.06/1.15 avg.
18,000/5.3/1.5 peak



Full Cube
1.25" x 1.25" x 1.25"

X SERIES

GBX1060 - ICE MACHINE

THE X-SERIES SIGNATURE

Produces up to 1,000lbs of ice per day. The X-Series from Kold-Draft features rounded corners, plastic top panels, plastic louvers and an LCD display. X-Series machines are stackable with other X-Series machines. Double the capacity in the same footprint.

GBX1060 Series Daily Capacities: Lbs of Ice per 24 Hours per Unit

Model Number	Electrical Volts/Hz/Ph	Condenser	Ice Capacity 24 Hours lbs (kg)		Energy Input 90°F (32°C) 70°F (21°C) kWh/100 lbs (kJ/kg)	Water Use gal/100lb (l/kg)		Min. Circuit Amp	Max. Fuse Size Amps	Required Condenser
			70°F (21°C) 50°F (10°C) Ambient/Water	90°F (21°C) 70°F (10°C) Ambient/Water		90°F (32°C) Potable	70°F (21°C) Condenser			
GBX1064ACE	208-230/60/1	Air	818 (371)	711 (323)	4.96 (393)	12.5 (1.1)	N/A	8.2	15	N/A
GBX1064LCE	208-230/60/1	Liquid	816 (369)	774 (351)	4.09 (325)	13.03 (1.1)	120.08 (10)	7.0	15	N/A
GBX1064RC	208-230/60/1	Remote	959 (435)	767 (348)	5.3 (421)	12.6 (1.1)	N/A	11.0	25	RC314APV

Dimensions/Weight

Description	Dimensions W x D x H	Ship Weight
Air Cooled	42.3" x 31.1" x 33.7" (107.4cm x 79cm x 85cm)	360lb (163.3kg)
Liquid Cooled	42.3" x 25.7" x 33.7" (107.4cm x 65.3cm x 85cm)	320lb (145kg)
Remote	42.3" x 25.7" x 33.7" (107.4cm x 65.3cm x 85cm)	320lb (145kg)

Recommended Operating Requirements

Description	Minimum	Maximum
Room Temperature	45°F (7°C)	110°F (43°C)
Water Temperature	45°F (7°C)	90°F (32°C)
Voltage 208-230	198V	253V
Voltage 115	104V	126V
Potable Water Pressure	20 PSIG (137 kPa)	100 PSIG (689 kPa)
Liquid-Cooled Condenser Pressure	20 PSIG (137 kPa)	100 PSIG (689 kPa)

Compatible Storage Bins

Model Number	Dimensions W x D x H*	Capability	Ship Weight
KDB650	42" x 35" x 41" (106.9cm x 88.9cm x 104.1cm)	650lb (294.8kg)	182lb (82.6kg)
KDB950	48" x 31.75" x 50" (121.9cm x 80.7cm x 127cm)	950lb (431kg)	230lb (104.3kg)

*Height includes 6" (15.2cm) legs

Accessories

Model Number	Description	Ship Weight
102149501	GBX560/GBX1060 Series on top of GBX560/GBX1060 Stacking Kit	5lb (2.3kg)
DR3-GB	GB/GBX Series Drain Riser Kit, 3"	20lb (9kg)

KOLD-DRAFT recommends all ice machines have water filtration. Please reference water filtration specification sheet.



KOLD-DRAFT

101 Corporate Woods Parkway, Vernon Hills, IL 60061
1-800-840-9577 | info@kold-draft.com | www.kold-draft.com



KD SS GBX1060 01-26