

Energy efficient, eco-friendly hydrocarbon refrigerant with low charge, spark-free components, providing the greatest reliability. Designed with detailed quality to meet all food safety requirements of the foodservice industry.



KEY FEATURES



Electronic Temperature Control

Ensures optimal equipment performance by maintaining products at the ideal temperature for consumption.



Eco-Friendly Refrigerant

Environmentally friendly hydrocarbon refrigerant has low Global Warming Potential (GWP). Meets all USA refrigerant and energy standards.



Electronic Fan Motors

These motors provide improved performance by using only a fraction of the energy required by shaded pole motors.




LED Lighting

Our patented LED system uses a fraction of the energy and has over ten times the lifespan compared to a fluorescent light bulb.



Stainless Steel Material

High-quality material for food preservation, complying with safety and hygiene standards.



Cyclopentane Insulating Foam

It is eco-friendly as it does not contain Chlorofluorocarbons (CFC) or Hydrofluorocarbons (HC) and is a highly efficient insulator.

TECHNICAL SPECIFICATIONS

Exterior Dimensions		Interior Dimensions		Usable Interior Capacity	
H: 83 1/8"	211 cm	H: 61 3/8"	156 cm	H: 54 3/4"	139 cm
W: 27 1/2"	70 cm	W: 23 1/4"	59 cm	W: 22 1/2"	57 cm
D: 35 3/8"	90 cm	D: 27 1/8"	69 cm	D: 25 1/4"	64 cm

Usable Volume	23.4 ft ³	662.6 lts
Doors	1	
Door construction	Solid Stainless	
Shelves	3	
Shelves Size	22 1/4"	56.5 cm
	24 3/4"	63 cm
External Material	Stainless Steel	
Internal Material	Stainless Steel	

REFRIGERATION PERFORMANCE DATA

Refrigerant	R290 2.1 Oz (0.060 kg)	
Energy Consumption	1.32 kWh/24h	
Compressor Power	1/4 HP	
Condenser	Dynamic	
Thermostat setting default	44.6°F (7°C)	32°F (0°C)

ELECTRICAL DATA

Power supply	115V / 60 Hz	
AMPS	2.2 A	
Cord length	118" (300 cm)	
Lighting	1 module, 72 LED per strip	
Plug type	NEMA 5-15P	
Controller	CIR EVO 2V0	


LOGISTIC DATA

Trailer Loads	53': 58			
Unit weight	Gross		Net	
	156 kg	343.9 lb	146 kg	321.9 lb
Dimensions w/packaging	H: 90 1/2"	230 cm		
	W: 33 7/8"	86 cm		
	D: 36 5/8"	93 cm		


*Energy consumption based on ANSI/ASHRAE Standard 72-2005.
 *Dimensions rounded up to the nearest inch or centimeter.
 *Specifications subject to change without notice.
 *H:Height, W:Width, D:Depth
 *Specifications subject to change without notice.

CONTACT INFORMATION
 IMBERA | 1925 Shiloh Road, Building #2 Kennesaw, GA 30144
 P: 678-504-6835

PRODUCT VIEWS



ADDITIONAL FEATURES



Black epoxy shelves



Mechanical Lock



4" Pre-installed Casters

Customer Service and warranty

Five-year limited warranty, includes parts and labor.
 An additional two-year warranty is issued on the compressor (USA & Canada only).
 Operators must follow installation and operational guidelines per Imbera User's Manual.
 It is essential that each cooler is directly connected to a single power supply; failure to do so will result in voiding the warranty.
 Customer service: 866.548.5770

24/06/2025