

safe temperature has been reached to destroy harmful bacteria. With magnifying lens and crisp dial faces or large LCD

stem to indicate the minimum insertion point. Digitals yield a faster response and provide greater overall accuracy with



	1246-02C	1246-03C
	Bimetal Pocket Test	Bimetal Pocket Test
	0° to 220°F (-20° to 100°C)	50° to 550°F (10° to 285°C)
	±2°F (±1°C)	±5°F (±3°C)
	Stainless Steel	Stainless Steel
	1" (25 mm)	1" (25 mm)
	0.150" (3.0 mm)	0.150" (3.0 mm)
	5" (127 mm)	5" (127 mm)
	Magnifying Polycarbonate	Magnifying Polycarbonate
	Yes Sheath Only	Yes Sheath Only
	0.5 oz (14 g)	0.5 oz (14 g)
	1 Year	1 Year

Digital



	DPS300	DT300
	Swivel Head Digital	Oval Style Digital
Temperature Range:	-40° to 302°F (-40° to 150°C)	-40° to 302°F (-40° to 150°C)
Accuracy:	±2°F (±1°C)	±2°F (±1°C)
Resolution:	0.1°	0.1°
Response Time:	<18 seconds	<20 seconds
Stem Length:	4.75" (121 mm)	4.625" (117 mm)
Shaft Diameter:	0.150" (3.8 mm)	0.150" (3.8 mm)
Housing:	ABS Plastic	ABS Plastic
Power:	(1) 1.5V #LR44	(1) 1.5V #LR44
Auto Shut-Off:	10 min	-
Display LCD:	0.5" (13 mm)	0.875" (22 mm)
Weight:	1 oz (28 g)	0.5 oz (14 g)
Regulatory Listings::		
Warranty	1 Year	1 Year