



Project: _____

Model: _____ Series #: _____

Dealer: _____ Quantity#: _____

Delivery address: _____ Date: _____

Bottom Mounted Series Reach in Solid door

Model#KM-72RF(Refrigerator and Freezer)



Features

- Precision ventilated refrigeration system keeps food at safe temperature
- Electronic control system make it easy to adjust temperature set point and defrost frequency
- Self closing door with 90 degree stay open feature,locks and keys included
- Preinstalled heavy duty casters with brakes
- Removeable installation board makes it easy to access condenser coil for cleaning and service.
- Stainless steel exterior and interior, ensure longer life
- Top mounted LED light,goes on when door open,goes off when door closed
- Anti-corrosion coated copper coil evaporator, ensure 10 years life of westlake products
- 9 epoxy coated steel wire shelves,90 lbs loading capacity each.
- R290 hydro carbon refrigerant that has zero(0) ozone depletion potential(ODP) & three(3) global warming potential(GWP)

WARRANTY:

- 2 Years Parts and Labor
- 6 Years compressor (Additional 4 years parts only)
- westlake is responsible for components failure. but is not responsible for improper operation failure and artificial damage.



Parts & Labor



Compressor



Intertek



Intertek

Conforms to UL&NSF-7 Standards





Bottom Mounted Series Reach in Solid door

Model#KM-72RF(Refrigerator and Freezer)

TECHNICAL DATA

SKU	WK-72RF
Model #	KM-72RF
Temperature range	33~41°F-8~0°F
Refrigerant	R290
Max Ambient Temperature	100°F
Defrosting	Auto Defrost
Horsepower	1/6P+1/4P
Exterior Dimension	72.8*31.5*78
Interior Dimension	45.3*23.2*56.3/21.3*23.2*56.3
Gross Weight	521lbs
Net Weight	437lbs
Packing Dimension	76*34*82
Voltage/Phase/Hz	115V/1/60Hz
Amps	7.0
Plug Type	NEMA 5-15P
Electrical Cord Length	70.8

PLAN VIEW

