



223 W Rosecrans Ave., Gardena, CA 90248
T. 310-808-0102 www.blueairfse.com

Project: _____
Location: _____
Item #: _____
Model #: _____ Qty: _____
AIA #: _____ SIS #: _____
CSI Section 11400

Bottom Mount Reach-In Refrigerator

Model
BSR72-HC

Model

BSR72-HC

Cabinet Construction

- Stainless steel interior and exterior (galvanized steel back & bottom).
- High-density, HFC-free cyclopentane insulation.
- Epoxy-coated wire shelves with adjustable height.
- Four (4) wire shelves per section.
- Six (6) 4" diameter swivel casters with front brakes.

Refrigeration

- Hydrocarbon refrigerant (R-290).
- Self-contained system, bottom-mounted compressor. Electrodeposition-coated evaporator increases performance by maintaining the heat transfer rates over the life of the evaporator and reducing potential corrosion.
- Bottom-mounted condensation pan.
- Designed to prevent water overflow and increase ventilation.
- Innovative hot gas frame heating system reduces condensation and increases energy efficiency.

Doors

- Alarm sounds when doors are not completely closed to protect against food spoilage.
- Self-closing doors (doors close at 90° or less).
- Automatic hold-open door feature at 110°.
- Durable, easy-to-replace door gasket.
- Lifetime-guaranteed, heavy-duty, all-metal door handles (Ni-Cr-plated).
- Door designed for easy opening.
- Doors equipped with pressure relief valves to eliminate vacuum pressure.
- Standard door locks.

Design & Features

- LED interior lighting.
- Self-diagnostic digital temperature control and monitoring system.
- Digital display allows for easy monitoring.
- Digital controls include manual defrost for easy maintenance.
- Rounded corner design gives a stylish appearance and reduces chances of injury.

Temperature range of 33°F to 39°F

- Air guard on rear wall ensures proper air circulation and cooling.




Model	Doors	Shelves	Capacity (Cu.ft.)	HP	AMPS	W x D* x H† (inches)	Crated Weight (lbs.)
BSR72-HC	3	12	72	1/2	5.5	82 ⁵ / ₈ x 31 x 77 ³ / ₄	653


Bottom Mount Reach-In Refrigerator

PLAN VIEW


(Unit: inches)



TOP VIEW



FRONT VIEW



SIDE VIEW

Model

BSR72-HC

Voltage	115V/60Hz/1ph
NEMA Config.	 NEMA 5-15P
AMPS	5.5
HP	1/2
Cord Length (ft.)	9.8
Refrigerant	R-290
Ext. Width (inches)(mm)	81 1/8 (2060mm)
Ext. Depth (inches)(mm)*	31 (787mm)
Ext. Height (inches)(mm)†	77 3/4 (1976mm)
Doors	3
Shelves	12
Net Capacity (cu. ft.)	72
Net Weight	615 lbs. (279 kg)
Gross Weight	653 lbs. (296 kg)

Specifications subject to change without notice.

* Depth does not include 1-1/2" for door handles. † Height does not include 5" for caster height.

Warranty

5 Year Parts and Labor Warranty
7 Year Compressor Warranty

Standard Features

- Six (6) 4" diameter casters with front brakes
- Door locks
- Hot gas frame heating system
- Self-contained system

Optional Accessories

- 2" dia. stem casters:
 8020-21-HDP (without brake), 8020-21-HDP-TLB (with brake)
 Overall height: 80-5/8" (2049mm)



223 W Rosecrans Ave., Gardena, CA 90248
 T. 310-808-0102

 blueairfse.com
 orders@blueairfse.com