BAKE TECH INNOVATION
4184 E. Conant St., Long Beach, CA 90808
www.baketechinnovation.com

BTDO-202U

DECK OVEN

STANDARD FEATURES

Advanced Digital Control
* Simultaneous display of actual and set temperatures.
* Programmable timer, memory functions, and optional steam injection control for flexible baking operation.

Large Viewing Glass Door
* Large tempered glass window for product monitoring.
* Spring-assisted door designed for smooth opening and closing.


Steam Injection System (Optional)
* Optional steam injection system designed to support a variety of baking applications requiring humidity control.

Ceramic Hearth Deck (Optional)
* Optional ceramic hearth deck designed to retain heat and provide a traditional baking surface.




MODEL	BTDO-202U
Exterior Dimension(s) (L x D x H) (inch(mm))	54 7/8 x 40 3/4 x 77 (1395mm x 1036mm x 1955mm)
Capacity	4
Electrical Requirements	220V, 3PH, 60Hz
KW	10Kw
AMP	26Amp
MIN, SUPPLY WIRE SIZE (AWG)	AWG 12
Tray Size	18" x 26" (460mm x 660mm)
Temperature Range	90ºF - 536ºF
Preset	4
Net Weight	1148 lbs
Water Inlet	1/2" PT (BSPT) (OD 0.59" (15mm))


- Design and specifications subject to change without notice.
- Most updated spec sheets are available at www.baketechinnovation.com
- Actual shipping weight may differ due to extra packing materials for product protection.
- Extra lead time will apply, please call factory for more details to order.
- 1 Year Parts and Labor Warranty




FRONT VIEW



SIDE VIEW



TOP VIEW



REAR VIEW

CHAMBER SIZE (EACH DECK)

38.2" x 28.7" x 9" (970mm x 730mm x 230mm)