










| Model | Alade | Cutting cto | 55 section Food thute | Chuites | kođpini | Overall diff | ensions Netwel | Poner Poner |
|-------|-----------|----------------------|-----------------------|--------------|---|---|-------------------|-------------|
| | in mm | in mm | in mm | in mm | in/mm | in/mm | Lbs Kgs | Нр |
| SST12 | 12 300 | 9.44x6.29 240x160 | 9.84x10.03 250x255 | 12.99 330 | A 22.24/565 B 14.96/380 H 18.50/470 | A 25.59/650 B 22.04/560 H 18.50/470 | 63.93 29 | 1/2 |

Cord & Plug: Attached 5.5 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-1 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-1 flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-1 flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-1 flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-1 flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-1 flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-1 flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-1 flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15. Voltage: 115-60-1 flexible 3-wire cord with molded plug fits a grounded receptacle 3-wire cord with molded





PROFESSIONAL GRAVITY SLICER - MANUAL GEAR DRIVEN







SST12 is a premium heavy-duty manual slicer.

The SST-Series line of premium slicers from Rheninghaus delivers precision, performance, industry-leading convenience, superior cleanability and lasting value.

The special protections make it suited for humid environments. Ideal for deli shops, supermarkets, restaurants, hotels, catering companies.

- Anodized aluminium casting construction: sturdy and light weight.
- 12" high quality hardened chromium steel alloy blade.
- Permanently attached knife ring guard.
- 0 to 9/16" slice thickness.
- Powerful and noiseless continuous use motor.
- Insulated switch. Overload protection manual reset.
- Gear drive: long life, no maintenance.
- Carriage smooth glide motion also with heavy products.
- Large clearance between the back of the blade and the base provides access for easy cleaning.
- Slice thickness precision adjustment: gasket-sealed mechanism.
- Drip deflecting edge of the gauge plate: adjustment mechanism is protected.
- No-drip edge base: easy cleaning.
- Stainless steel ball-bearing blade pulley and special moisture-proof gasket.
- Built-in sharpener, removable for cleaning purposes.
- 30° carriage angle: good visibility of the slice exit area and better ergonomy.
- Non-slip rubber feet.

