



BLS-4FLD-1H

XAKHT-HCFS: Full Size Ventless Hood for LED/TOUCH Convection Ovens

Water Connection is required for proper installation, filtration is highly recommended to prevent scale build up. Drain line or floor drain is needed.



UL 710 Emissions



Water Consumption Note* 10.3 oz from 3 hours and 30 minutes from the baking cycle. Therefore you would need to put the water consumption at less than 3 oz per hour.



LED digital programmable controls:



3 BAKING STEPS

0-20-40-60-80-100% HUMIDITY

0 - inf TIMER

2 FAN SPEEDS

120° - 500° F TEMPERATURE

PROOFER CONTROL

99 PROGRAMS
12 QUICK ACCESS



NEMA 6-50P Plug

Holds Full size 18x26 Sheet Pans

OST-195-C Heavy-Duty Stand with Wheels

- Handles 10 full size 18x26 sheet pans (not included)
- Aluminum

Made to Cadco Ltd. specifications by UNOX S.p.A., Italy • NSF, MET to UL & CSA Standards
We recommend that the end user have a standard ice-machine filter when using a humidity hookup.

Bakerlux Station Includes:

| Model | Color | Volts | Watts | Amps | Unit Dimensions |
|--------------|-----------|---------|-------|------|---------------------------------|
| XAFT-04FS-LD | Stainless | 208-240 | 7600 | 32 | w:31 1/2", h:19 5/8", d:35 1/2" |
| OST-195-C | Stainless | N/A | | | w:30" h:40 x d:27 |
| XAKHT-HCFS | Stainless | 208/240 | 200 | 1 | w:31", h:10", d:34" |



Shipping Unit Dimensions

2 SKIDS CLASS 200

1 SKID 44X38X56 260 POUNDS - 1 OVEN, HOOD AND STAND

1 SKID 44X38X29 200 POUNDS - 1 OVEN AND STACKING KIT