



Your Solutions Partner

Specifications

F.O.B. Sedalia, Missouri 65301



HEAT IN BASE MODULAR UNIT:

- For hot food and solid top units
- Accommodates (4) 6"D pans; (6) 4"D pans; (12) 2" D pans
- Includes electric outlet in cabinet base when ordered with steamtable
- Available as stand-alone retrofit for hot food or solid top units already in field
- (2) units can be used in 5- or 6-well units



SKELETON UNITS

- Heavy gauge paint-grip or stainless steel
- Finish to match other units
- Available on legs only
- Specify length up to 132"



3-BAR TRAY SLIDES

- 18", 30", 32", 46", 60", 74", 88" standard lengths
- 1" diameter stainless steel tubes, end capped
- Stainless steel brackets
- Special lengths available

DUKE MANUFACTURING CO.

2305 N. Broadway
 St. Louis, MO 63102
 800.735.3853 Toll Free
 314.231.5074 Fax
 www.dukemfg.com
 SS-1179 Thurmaduke - Accessories

Approval Stamp(s):

PRODUCT INFORMATION:

PROJECT: _____

ITEM: _____

QUANTITY: _____

MODEL:

Thurmaduke Serving Systems

Accessories

- HTD-BASE-M** Heat-in-Base modular unit
- 328PG/SS-OP** Sliding doors - Operator's side, S/S or paint grip
- 328PG/SS-CU** Sliding doors - Customer's side, S/S or paint grip
- TS380-PG/SS** Skeleton unit - S/S or paint grip
- TS381-PG/SS** End return - S/S or paint grip
- TS3BTS-HD** Tubular tray slides, S/S hinged brackets
- TS3BTS-FX** Tubular tray slides, S/S fixed brackets
- TSSOLID-HD** Solid tray slides, S/S hinged brackets
- TSSOLID-FX** Solid tray slides, S/S fixed brackets



SLIDING DOORS:

- Double-wall, paint grip or stainless steel
- Ball-bearing wheels on overhead tracks
- Lift out for easy cleaning
- Recessed stainless steel pull
- Lock option at added charge



SOLID TRAY SLIDES:

- 18", 30", 32", 46", 60", 74", 88" standard lengths
- Heavy gauge stainless steel, stainless steel brackets
- (2) 1/8" high embossed rubbing tracks
- Special lengths available

Agency Listings:



Specification subject to change



REV B 04/20/2020



THURMADUKE SERVING SYSTEMS Accessories

A.I.A. File No. 35-C-13

Heat in Base Unit: 120 volt, 1 phase, 300 watts, 2.5 amps, 6 ft. cord set NEMA #5-15P

Freight Class: 150

Model	Left to Right		Height		Depth		Cutout Length		Cube crated ft.	Weight	
	in	cm	in	cm	in	cm	in	cm		lbs	kg
HTD-BASE-M	30	76.2	17	43.2	23	58.4	33-1/8	84.2	35.4	190	86.0

Skeleton Units

Freight Class: 150

Model	Description
380-25	Front panel: 36" high, 12 lbs. per foot - must attach to adjacent unit
381-25	End panel: 32" wide, 36" high, 4" long, 20 lbs. w/6" legs

Catalog No. TSS-ACCESS

Sliding Doors - for Hot Food

Sliding Doors - for Solid Top, Cold Pan and Urn Stand

Model	Length		Door Height		Weight		Model	Length		Door Height		Weight	
	in	cm	in	cm	in	cm		in	cm	in	cm	lbs	kg
328-3	46	116.8	12	30.5	40	18.2	329-3	46	116.8	17	43.2	45	20.5
328-4	60	152.4	12	30.5	50	22.7	329-4	60	152.4	17	43.2	55	25.0
328-5	74	188.0	12	60.5	60	27.3	329-5	74	188.0	17	43.2	65	29.6
328-6	88	223.5	12	30.5	70	31.8	329-6	88	223.5	17	43.2	75	34.1

Tray Slides with Brackets - Fixed (FX) or Hinged (HD)

Freight Class: 85

Number of Sections			2	3	4	5	6
Length of Body Unit	18"/45.7 cm	30"/76.2 cm	32"/81.3 cm	46"/116.8 cm	60"/152.4 cm	74"/188.0 cm	88"/223.5 cm

TUBULAR - THREE 18 GAUGE STAINLESS STEEL TUBES (ENDS CAPPED) Weight: Approx. 7 lbs (3.2 cm) per foot. 12"W / 30.5 cm

SOLID - 16 GAUGE STAINLESS STEEL WITH TWO 1/8" (.13 CM) DIE-FORMED RUBBING TRACKS

Weight: Approx. 12 lbs (5.5 kg) per foot (30.5 cm), 12 -1/4" / 31.1 cm Wide - Adds 13" (33.0 cm) to width of unit

NO OF BRACKETS PROVIDED FOR TUBULAR OR SOLID TRAY SLIDES	2	2	2	2	2	3	3

NOTE: Each additional foot of Tray Slide includes required number of brackets. Maximum recommended span between brackets is five (5) feet (152.4 cm). For continuous Tray Slide, add one bracket at end of counter plus one bracket for each unit. Add one additional bracket for each unit that is longer than 60" (152.4 cm).

SPECIFY IF BRACKETS ARE TO BE SHIPPED LOOSE OR MOUNTED TO TRAY SLIDE. If brackets are to be mounted, please supply a sketch (with measurements) of their exact locations.

THURMADUKE SERVING SYSTEMS - ACCESSORIES



Your Solutions Partner

Duke Manufacturing Co.

2305 N. Broadway
St. Louis, MO 63102

Phone: 314-231-1130

Toll Free: 1-800-735-3853

Fax: 314-231-5074

www.dukemfg.com

Printed in U.S.A

© 2020, Duke Manufacturing Co.