



# QUOTE DRAWING

Sign below for acceptance

X \_\_\_\_\_

Door hinge: Left \_\_\_\_\_ Right \_\_\_\_\_

Door location wall (centered): Left \_\_\_\_\_ Front \_\_\_\_\_

By signing here, you agree to our terms and conditions as outlined on [www.uscooler.com/terms](http://www.uscooler.com/terms). Panel configuration subject to U.S. Cooler final approval. A facsimile or emailed approval of this drawing FO1014FL.PA110 shall have the same force and effect as a signed original and shall, upon receipt by U.S. Cooler, be binding on both parties.

Materials:  
ExtMetal:Galvalume  
IntMetal:Galvalume  
Foam:Extruded 4in.

Legend  
Ceiling \_\_\_\_\_  
Floor \_\_\_\_\_

Freezer: 13'-8 1/2" x 9'-9 1/2" x 7'-6"

Scale: 1/4" = 1'



**FASTCOOLER**

by U.S. Cooler

401 DELAWARE ST. \* QUINCY, IL 62301

TEL 217-228-2421 \* 800-521-2665 \* FAX 217-228-2424

CUSTOMER

JOB#

P.O.#

DATE

04/03/2020

DRAWN

C.G. 1.0

DWG. REF

FO1014FL.PA110

APV.

To aid in packing, please indicate with an X the corner where installation will be starting.

Refrigeration Specifications								
Qty	Manufacturer	Model	HP	Electrical	MCA	CmpRLA	CmpLRA	Dimensions DxWxH
Pre-assembled Remote Low Temp R404A Air Cooled Outdoor Condensing Unit								
1	Russell	RFO350E4SDA	3.5	208-230/1Phase/60Hz		21.2	104	33"x43.875"x35"
1	Russell	RL6E090DEAA		208-230/1Phase/60Hz	10.8			15.5"x43.625"x18.125"