

NON-HEATED PATIENT TRAY DELIVERY CABINETS

15"x 20", 14"x 18", or 18"x 26" Size Patient Trays, Double Deep

DOUBLE DEEP – NON-HEATED / NON-INSULATED "ETC-1520" SERIES

FWE's quiet ride, all stainless steel meal delivery carts provide maximum reliability and are perfect for locations that require concentration and tranquility

- 1** Versatility – fixed stainless steel tray racks hold wide varieties of trays, double deep. Fixed rack widths are easily adjustable on alignment pins to accommodate tray changes in your healthcare operations
- 2** Cleanability – stainless steel is favored by operators because it does not rust and is easy to clean. Other sanitary standard features include: antimicrobial magnetic door handles, lift-off doors and pitched center drain with plug
- 3** Mobility – even when fully loaded, these carts move with ease. 6" corrosion resistant casters mounted to stress plates absorb shock and reduce noise during room service delivery. Hidden, magnetic door hold open feature allows for compact unloading and out-of-the-way in hallways
- 4** Noise suppression – FWE's patient tray delivery carts feature standard sound dampening components that eliminate metal-on-metal noise potential: latchless door design, rubber door stoppers, rack grommets and quiet casters
- 5** Hospitals need durable foodservice equipment. FWE's food delivery carts take the abuse of any transport application. Standard features include: tubular welded stainless steel frame, full perimeter bumper, heavy-duty stainless steel hinges, solid tubular push bar handle and vented ends (allows excess heat and moisture to escape)
- 6** Serve hot and cold foods together using pellet systems, insulated or disposable containers - prepare meals ahead of time, then easily and quietly transport to serving location


**Two year limited warranty*



Two-door models:
MASTER CASTERS

NEW CASTERS!
MASTER CASTERS make the heaviest two-door models glide with ease, even when fully loaded!
VISIT FWE.COM/CASTERS TO LEARN MORE

One-door models:
QUIET RIDE CASTERS




Adjustable Fixed Rack Width



Antimicrobial Door Handle



Pitched Center Drain with Plug



Corrosion Resistant, Quiet Casters

SPECIFICATIONS

NON-HEATED PATIENT TRAY DELIVERY CABINETS



MODEL NUMBER	TRAY SIZE [A]	TRAY CAPACITIES [B]	OVERALL EXTERIOR DIMENSIONS IN. (mm) (Height Includes Casters)			CLASS 250		
			HIGH "H"	DEEP "D"	WIDE "W"	NO. OF DOORS	CASTER SIZE	SHIP WT. LBS. (KG)
	15" x 20" or 14" x 18"	10	39.25"	36.25"	30.75"	1	6"	210 (95)
	18" x 26"	5	(939)	(921)	(749)			
	15" x 20" or 14" x 18"	12	44.5"	36.25"	30.75"	1	6"	215 (98)
	18" x 26"	6	(1080)	(921)	(749)			
	15" x 20" or 14" x 18"	14	47.75"	36.25"	30.75"	1	6"	260 (104)
	18" x 26"	7	(1219)	(921)	(749)			
	15" x 20" or 14" x 18"	16	53"	36.25"	30.75"	1	6"	300 (136)
	18" x 26"	8	(1321)	(921)	(749)			
	15" x 20" or 14" x 18"	20	63.5"	36.25"	30.75"	1	6"	310 (141)
	18" x 26"	10	(1590)	(921)	(749)			
	15" x 20" or 14" x 18"	24	42.5"	35.5"	54.5"	2	6"	370 (168)
	18" x 26"	12	(1080)	(902)	(1340)			
	15" x 20" or 14" x 18"	32	53"	35.5"	54.5"	2	6"	380 (171)
	18" x 26"	16	(1321)	(902)	(1340)			
	15" x 20" or 14" x 18"	40	63.5"	35.5"	54.5"	2	6"	450 (202)
	18" x 26"	20	(1590)	(902)	(1340)			


[A] Fixed rack assembly accommodates 15"x20", 14"x18", or 18"x26" trays by adjusting the position of the racks on the alignment pins.

[B] Model numbers are based on capacities @ spacings of 5.25". Other spacings are available at time of order.



[C] Trays not included. Contact individual manufacturers for trays. Sample tray(s) required with order.

Pass-thru Door [add "P"] is available. Consult factory.

SWIVEL CASTERS ON REAR:
ETC-1520-10, ETC-1520-12, ETC-1520-14,
ETC-1520-16, ETC-1520-20



SWIVEL CASTERS ON BOTH SIDES:
ETC-1520-24, ETC-1520-32, ETC-1520-40



CONSTRUCTION. Heliarc welded, single unit construction of 18 gauge stainless steel. Welded tubular base frame shall be 1" square, heavy gauge stainless steel tubing, with 10 gauge stainless steel reinforcing plates at corners and fittings. Cabinets shall have vented ends on each side of the unit.

HANDLES. Heavy-duty, 1" diameter tubular stainless steel push handles: ETC-1520-10 and ETC-1520-12 shall have one (1) handle on the top of the unit. ETC-1520-14, ETC-1520-16, and ETC-1520-20 shall have one (1) handle on the rear of the unit. ETC-1520-24, ETC-1520-32, and ETC-1520-40 shall have two (2) handles, one mounted on each end of the unit.

BUMPER. Solid continuous wraparound aluminum channel, bolted to frame, with snap-in, non-marking replaceable vinyl cushion. Full perimeter bumper extends beyond doors, handles, etc., for added protection. Shall be continuous, with corner cut-outs to facilitate cleaning.

DOORS AND LATCHES. Flush mounted, stainless steel insulated doors. Each door shall have two (2) heavy-duty, lift-off, 12 gauge stainless steel hinges. The hinge mountings are reinforced with stainless steel backing plates. Each door shall be equipped with a positive closing, flush-in-door, antimicrobial magnetic door handle. Each door shall be equipped with a hidden, magnetic door hold open feature.

CASTERS. Single-door models shall have maintenance free, Cart Wash casters with stainless steel bearing, in a configuration of two (2) rigid and two (2) swivel with brake. Two-door models shall have maintenance free, Master Casters with sealed precision ball bearing, in a configuration of two (2) rigid and four (4) swivel with brake. Casters shall have a reinforced yoke mounted to 10 gauge caster plate. The caster mounting plate shall be secured to a 10 gauge stainless steel reinforcing stress plate via welded-in-place stainless steel studs. The reinforcing stress plates shall be welded to the heavy gauge tubular frame of the unit.

TRAY SLIDES. Fully welded, unitized tray slide assemblies shall be heavy gauge stainless steel, channels fixed-in-place at 5.25" spacings and shall be capable of field adjustability to accommodate two (2) 15" x 20" or (2) 14" x 18" trays or (1) 18" x 26" tray per pair of tray slides. Each rack assembly contains four (4) sets of alignment holes that mount to fixed top and bottom alignment pins welded to cabinet floor and ceiling. Racks with custom tray spacings are available (consult factory).

PITCHED DRAIN. Pitched center drain with plug to facilitate thorough cleaning of interior. Models with one (1) door shall have one (1) pitched center drain. Models with two (2) doors shall have two (2) pitched center drains.

INSTALLATION. Unit should not be installed in an area where adverse environmental conditions are present.

DOORS

- Pass-thru door
- Key-locking door latch
- Paddocking transport latch
- Paddle latch
- Alternate door swing configurations

SPACINGS

- Uprights with adjustable tray slides (option available at no additional cost)
- Custom tray rack spacing

CASTERS

- All swivel or larger casters
- Master casters (single door models only)

EXTRAS

- Security packages
- Cold plate cartridge
- Menu card holder
- Dry erase board
- Grounding strap
- Top guard rail (3 or 4 sides)
- Top corner bumpers
- Beverage urn angles (on select models)