



VALPRO COMMERCIAL REFRIGERATION

203 Kelsey Ln., Building G
Tampa, FL 33619
813-502-0300
Toll Free 1-888-VALPRO-8
www.ValproRefrigeration.com
sales@ValproRefrigeration.com

PROJECT:	
MODEL #:	
ITEM #:	QTY:
AVAILABLE W/H:	
APPROVAL:	

THREE DOOR REACH-IN FREEZER

MODEL: VP3FDV-HC

We are proud to introduce the beautifully constructed **Valpro VP3FDV-HC**. All our models are manufactured with uncompromising quality, energy efficient technology, and standard premium features built in. This model will provide many years of worry free service and delivers cost saving energy efficiency. All models are energy verified and deliver low operating costs. This unit utilizes natural hydrocarbon R290 refrigerant. All Valpro products are manufactured under strict ISO9001 standards for quality assurance, and to consistently deliver to our customers products that satisfy all expectations. All our products are operated, extensively monitored, and undergo rigorous inspection prior to packaging and shipping.

KEY FEATURES

- Durable stainless steel exterior, and 304 stainless steel interior cabinet
- High efficiency bottom mounted condensing unit installed on slide out rack for quick and easy maintenance
- Bottom mount compressor operates in coolest area possible and provides better efficiency and ergonomics
- Uniform temperature with larger efficient ECM fan motors and larger fan blades for superior air flow with faster recovery time
- 9 Heavy duty, epoxy coated wire shelves supported by pilasters for easy 1/2" adjustability and to sustain maximum loads
- Self closing doors with remain open feature past 90° for easy access loading and unloading
- Top mount quality door locks for added security
- Snap-in magnetic door gaskets removable and replaceable without tools for ease of cleaning
- LED interior cabinet lights standard all on models
- Electronic thermostat digitally controlled temperature system maintains optimum temperature with easily viewed LED display
- Standard 4" heavy duty casters, front locking, make it easy to move and clean underneath
- Oversized balanced refrigeration system uses double voltage 115/208-230/60/1 with NEMA L14-20P plug
- Automatic condensate evaporation system
- Door frame integrated heating element eliminates any condensation
- High density 2.4" foamed in-place CFC and HCFC free polyurethane insulation
- Energy Verified efficiency and ETL certified to NSF Standard 7



WARRANTY
2 YEAR Parts & Labor
5 YEAR Compressor



Model:
VP3FDV-HC

Three Door Reach-In Freezer

Bottom Mount Compressor - Three Door - Stainless Steel

Technical Data

Dimensional Data

Exterior Dimensions	81"W x 32.7"D x 82.3"H
Interior Dimensions	76.4"W x 27.6"D x 50.2"H
Net Storage Capacity	72 cu. ft.
Net Weight	563 lbs.
Crated Weight	624 lbs.
Shipping Dimensions	83.7"W x 34.1"D x 84.6"H

Refrigeration Data

Temperature Range	-10°F to +10°F
Refrigerant	R-290
Refrigerating System	Capillary Tube
Temperature Controller	Digital
Horsepower	1-1/4

Construction Data



Exterior Material	430 Series Stainless Steel
Interior Floor Material	304 Series Stainless Steel
Interior Wall Material	304 Series Stainless Steel
Insulation	2.4" CFC Free Polyurethane
Shelves	9 Heavy Duty Epoxy Coated

Electrical Data


Interior Lighting	Efficient LED
Amps (Watts)	4.8 (2025)
Voltage/Frequency/Phase	115/208-230/60/1
Plug Type	NEMA L14-20
Electrical Cord Length	9 ft.



FRONT VIEW



SIDE VIEW




PLAN VIEW



Specifications subject to change without notice.

CORRECT CONFIGURATION:
NEMA L14-20P
230/115/60/1



Valpro Commercial Refrigeration
203 Kelsey Ln., Building G
Tampa, FL 33619



Tel: 813-502-0300
1-888-VALPRO-8
www.valprorefrigeration.com