

Fusion

GMBS 52"H Dry Service Case

Structural Concepts®

- **GMBS452D** 48-3/4"L x 42-3/4"D x 51-3/8"H
- **GMBS552D** 60-1/2"L x 42-3/4"D x 51-3/8"H
- **GMBS652D** 73-1/8"L x 42-3/4"D x 51-3/8"H

(Lengths do not include 1-1/8" end panels)

Included

- LED top & shelf lights
- Lift-up front glass
- Non-refrigerated for ambient display
- One year parts & labor warranty
- Stainless steel rear exterior



Specify	Standard Features	Additional Options
EXTERIOR COLOR	• Powder coated (stock colors, specify RAL#)	• Laminated (non-premium) Confirm pattern/grain direction • Stainless steel
INTERIOR COLOR	• Black powder coated	• Stainless steel
LOWER FRONT PANEL COLOR	• Black powder coated	• Stainless steel
TRIM COLOR	• Black	• Silver
BASE	• Rail system for shims	
BUMPER FRONT	• 1" Boston bumper (specify color)	• 1" Stainless steel plate rail bumper
END PANELS	• None (specify per line-up)	• Cutaway w/ glass (LH / RH) • End bumper (LH / RH) • Full w/stainless steel interior (LH / RH)
FRONT GLASS	• Curved	• Flat angled
UPPER REAR	• Clear glass rear sliding doors	• Reflective glass rear sliding doors • Reflective glass rear sliding doors
PRICE TAG MOLDING	• None	• 1" Price tag molding (black or silver) • Universal price tag molding (clear w/ open top)
SHELVING	• 16" & 16" Solid shelving	• 16" & 16" Glass shelving
LIGHTS	• LED 3500K w/ frosted lens	• LED 4000K w/ frosted lens
ELECTRICAL CONNECT	• Electrical leads	
MISCELLANEOUS		• Front glass lock • Rear door lock

Fusion


GMBS 52"H Dry Service Case

Structural Concepts®



Intended Environment: Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.

Zone	Intended Product To Be Displayed	Warmest Avg Prod Temp ° F
1	Unpackaged non-refrigerated products	Ambient

PLAN VIEW



SIDE VIEW



NOTE: ALL DIMENSIONS APPROXIMATE

- ELECTRICAL JUNCTION BOX**
(SUPPLIED WITH 6" LEADS OR POWER CORD).
- LOCATION OF DRAIN TUBE FOR REMOTE REF.**
ONLY (SUPPLIED WITH 3/4" OR 1 1/2" PVC TUBE).

- REFRIGERATION LINE CONNECTION.**
- REMOTE FLOOR SINK & UTILITIES**
ACCESS AREA.

- SELF-CONTAINED CASE SERVICE ACCESS AREA.**
- DRY CASE SERVICE ACCESS AREA.**

Model Technical Specifications																
Model	L"	L1"	L2"	System Circuit Volts			Phs	Freq	Amps ***	Watts	Wires	NEMA Plug	SST	Conv. Rack BTUH	Para. Rack BTUH	Est Wt
GMBS452D	48.75	51.00	.00	Ambient/Lights (N/A)			1	60	0.70	33	2+G	Leads Single	N/A	N/A	N/A	N/A
GMBS552D	60.50	62.75	.00	Ambient/Lights (N/A)			1	60	0.99	120	2+G	5-15P or L5-15P	N/A	N/A	N/A	N/A
GMBS652D	73.13	75.38	.00	Ambient/Lights (N/A)			1	60	0.70	50	2+G	5-20P	N/A	N/A	N/A	N/A

*** Does not include electric defrost on freezer models.

Regulatory Approvals:

All Models ETL Listed to UL 65
ETL Sanitation to NSF/ANSI 2



DOE 2017
Energy Efficiency
Compliant

Important Notes:

- 1) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle.
- 2) 45" minimum door entry clearance required (without shipping skid).
- 3) Units must be shimmed during installation to ensure the unit is level and plumb.

⚠ WARNING: This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Note: Information is subject to change at any time. Visit www.structuralconcepts.com for the most current specs.

21874991

Revised 4-20-2022