

Marco POUR'D Install Checklist

Marco Beverage Systems requires that the following conditions are met before installation of the **POUR'D system** can begin. *Failure to meet these conditions may result in multiple visits by installers, the cost of which will not be covered by Marco Beverage Systems.*



SITE READINESS

- Minimum dimensions for cabinetry are 12 in. wide x 20 in. deep x 32 in. high.
 - If installing a shelf to hold the Control Box, ensure minimum 12 inches gap between it and the counter top.
 - The installation site should be safe, clean, and clear of all construction debris.
 - The site should no longer be an active construction zone.
-



POWER

- 110v AC service with NEMA 5-15 receptacle within 5 feet of installation location.
 - Power must be live to the outlets before installation.
-



WATER

- Dedicated 3/8" water supply line with shut off valve in place.
- Appropriate water filtration for the install location should be in place.
 - Water hardness should not exceed 5 grains per gallon.
 - Chlorides should be less than 30ppm.
- Incoming water pressure should be between 15 psi and 145 psi.
- If water lines and/or filtration are newly installed, ensure that the system is thoroughly purged before installation.



COUNTERTOP

- Holes must be present.
 - 1 ½ inch for the font
 - 4 inch for the drip tray*See Font install manual for cutsheet*
 - Counter thickness should not exceed 60mm
 - Holes should be within 150mm-500mm of the Control Box once installed.
-



DRAINAGE

- Drain should be located within one meter of the drip tray.
 - Drain must be installed below the level of the drip tray basin.
 - Drain must be an open gravity drain.
-



PRODUCT

- The connection point to the product must be no more than 4 feet from the product input fitting on the Control Box rear panel.
 - Intended product should be stored below the Control Box to avoid syphoning.
-



ADDITIONAL MODULES

- If installing the POUR'D system with a MIX boiler or FRIIA Chiller/Carbonator, refer to the site requirement documentation for those units as appropriate.

For questions, support, or additional resources – please reach out to Marco US Support.

us.support@marcobeveragesystems.com | +1 206-641-7677