

## BLAST CHILLER/SHOCK FREEZER ROLL-IN/ ROLL-THRU

VBCF-40-350  
VBCF-40-350PT

- Equipped with Secure-Temp 1.0™ Technology™
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Exclusive 2 Year Warranty on Santoprene Door Gaskets

**VICTORY ULTRASPEC™**  
FEATURING: **SecureTemp™ 1.0**

Secure-Temp 1.0™ is the industry's first and only full service temperature monitoring solution for your kitchen. Secure-Temp 1.0™ is standard on all Victory models and is HACCP compliant & meets NAFEM's data protocol.

**There are NO software or monthly monitoring fees.**  
Optional add on kits are available for additional units.

### STANDARD FEATURES

- Soft and Hard, Timed or Core Probe Blast Chilling
- Soft and Hard, Timed or Core Probe Shock Freezing
- Automatic Recognition of Core Probe
- Multi Point Sensor Temperature Display Button
- Core Probe Heater Button
- HACCP Alarm Display Button
- Pre-Cooling Cycle Button
- Adjustable Evaporator Fan Speed Button
- Timed Manual Defrost Button
- Infinity Mode Program with Adjustable Set Point
- Automatic Conservation Mode at End of Cycle
- On Board Recipe Book with 68 Pre-Set Programs
- 30 Free Memory Positions for Custom Programs
- LCD Illuminated Temperature Display
- Real Time Clock
- RS 485 Connection
- One, High Precision Heated 4 Point Multi Sensor Probe
- Adjustable Stainless Steel Feet



VBCF-40-350  
\*Shown with optional printer

### OPTIONS & ACCESSORIES

- Remote Models Air Cooled
- Printer Kit or USB Data Recorder/Interface
- UV Sterilization Lamp
- Core Probe for use with Vacuum Packaged Products
- Single Sensor Probes (up to 4 possible)
- Casters with Brakes
- Change Door Swing (Right Hinging Standard)
- 220/50 and 220/60 Models



Please refer to [www.energystar.gov](http://www.energystar.gov) to view the most up-to-date product listing and performance data

3779 Champion Blvd—Winston-Salem, NC 27105  
PH: (888) 845-9800 - Fax: (800) 253-5168  
sales@victoryrefrigeration.com    www.victoryrefrigeration.com

### VBCF CABINET CONSTRUCTION

AISI 30418/10 stainless steel exterior and interior. Die-formed interior floor has rounded corners and central drain for easy cleaning. High density foamed in place CFC and HCFC free expanded polyurethane insulation (3.2" thick). Anti-condensation perimeter heating around door opening. Nontoxic epoxy coated evaporator coil. Internal bumpers and external guards protect the cabinet interior and the control panel from mobile carts.

### VBCF DOOR CONSTRUCTION

Ergonomic door handle, safety panic button and outside lock, and rubber sweeper gasket.

### VBCF REFRIGERATION SYSTEM

The self-contained refrigeration system uses R404A refrigerant. Evaporator is fitted with high velocity fans for maximum cooling efficiency. Indirect air flow assures highest product quality.

### VBCF INTERIOR STORAGE ARRANGEMENTS

Accepts mobile carts—see model characteristics for cart sizes and pan capacity (number of pans and sizes). Cart(s) and pans not included.

### VBCF ELECTRONIC CONTROL SYSTEM

Highly visible and ergonomically positioned (recessed inside the door) electronic control with LCD display insures precise control of Blast Chilling (194 F to 37 F in 90 Minutes) or Shock Freezing (194 F to 0 F in 240 Minutes) Cycles. One touch hard and soft automatic blast chilling or shock freezing cycles based either on core probe temperature or timed cycle. Automatic recognition of the core probe and automatic conservation mode at the end of a cycle. One touch display of HACCP Alarms (power failure, cycle time out of HACCP required time, high temp, low temp) recorded in memory. The real time clock provides date, time, and duration of HACCP alarms (power failure, cycle time out of HACCP required time, high temp, low temp) recorded in memory. Will record up to 10 alarm events before over writing the first alarm and will keep the data for a minimum of 48 hours in case of a power failure. On board program memory holds 99 total programs. Adjustable Evaporator Fan Speed button allows for regulation of the fan during the blast chilling or shock freezing cycle. Compressor protected by overload cut-out with automatic reset. Micro-switch control cuts out the evaporator fan and compressor whenever the door is opened.

CHARACTERISTICS	VBCF-40-350	VBCF-40-350PT
Width, Overall (in.)	59.1	59.1
Depth, Overall (in.)	53.1	58.6
Height, Overall (with legs, in.)	87.8	87.8
Depth, Door Open 90°	85.8	85.8
Clear Door Height (in.)	75.6	75.6
Clear Cart Width (in.)	30.7	30.7
Internal Depth (in.)	41.3	41.3
Wall Thickness (in.)	3.1	3.1
Sheet Pan Capacity (18"x26")	20	20
Steam Table Pan Capacity (12"x20")	40	40
Chilling Capacity in 90 min (lbs.)	350	350
Freezing Capacity in 240 min (lbs.)	230	230
Capacity Mobile Cart(s)	1 GN 2/1	1 GN 2/1

### ELECTRICAL DATA

Cabinet Voltage	208-240/60/1	208-240/60/1
NEMA Plus	N/A	N/A
Total Amperes	5.2	5.2

### REFRIGERATION DATA

Refrigerant	R404A	F404-A
Refrigerant Capacity (W*)	9650	9650
BTUH	35584	35584
Climate Class	T	T

### CRATED DIMENSIONS

Crated H x W x D (in.)	91x59x72	91x64x72
Crated Weight (lbs.)	1258	1311
Uncrated Weight (lbs.)	924	946

VBCF Evap. Temp -10° F, Ambient Temp. 90° F

