

PR12 – *HEAVY DUTY* ALUMINUM PAN RACK







Construction

- Constructed of Heavy-Duty extruded 6063 aluminum alloy
- Choice exclusive Base Structure for rigidity and stability
- Available in both front-load and side-load styles
- Fully welded frame and base for strength
- Available in standard 70.5 inch or refrigerator 64 inch heights
- Available in 10, 11, 12, 15, 18, 20, and 25 tray capacities

Uprights & Cross Braces

 Heavy Duty (HD): All welded 1-1/4" square tubular frame with 1" cross braces with all rounded-edges

Casters

- **Heavy Duty (HD):** Heavy Duty 5" x 2" Polyurethane swivel casters
- Casters Bolted to Wheel channel

Runners

• Heavy Duty (HD): Runner angles measure 1-1/4" x 2" x .100" thick

EXAMPLE: PR12-A-1820-BKSB (Heavy Duty Aluminum Pan Rack, Front Load [21"W x 26"D], 20 Pan Capacity [3" Runner Spacing, 70.5"H], with Locking Brakes and a Solid Base)

EX. break-down: PR12-A - 18				20			- BKSB			
Heavy Duty Pan Rack	Pa	n Load Direction	Width	Depth	18x26 Pan Capacity	Runner Spacing	Height	Heavy Duty Rack Options		
PR12-A Aluminum Pan Rack	18 26	Front Load Side Load	21" 29"	26" 18"	10 10 Pan Cap. 11-64 11 Pan Cap.* 12 12 Pan Cap. 15 15 Pan Cap. 18-64 18 Pan Cap.* 20 20 Pan Cap. 25 25 Pan Cap. *64 inch height designed for	6" 5" 5" 4" 3" 2.5"	72" 64" 72" 72" 64" 72" 72"	AT Aluminum Top ST Stainless Top PT Poly Top 620U Heavy Duty 6" x 2" Poly-U Plate Caster BK Locking Brakes (2) VB Vertical Bumpers B Corner Bumpers (w/plate casters or solid base) SB Solid Base SBCB Solid Base w/ full perimeter bumper TGA Tray Guard for Aluminum Racks BLK Black Powder Coat ** GREEN Green Powder Coat ** Multiple Pan Rack Options may be selected by writing each option code subsequently without dashes or spaces. For example, if you want a Pan Rack with locking brakes and a solid base, you would write in the box below: BKSB ** other powder coat colors available, contact factory		
Sele	ect a c				eavy Duty Alumin			nber your Heavy Duty Aluminum Pan Rack		
PR12-A	-							-		
PR12-A	-			,				-		



LIMITED WARRANTY

Choice Equipment Company, Inc. warrants to the original purchaser that all of its goods and services sold shall be free of defect in material or workmanship during the twenty-four (24) months, twelve (12) months on wheels and casters, from the date of shipment or performance, provided the product has been used within the following restrictions:

- 1. The product was used for its intended purpose.
- 2. The product was properly handled, stored, installed, maintained and operated.
- 3. The product was not loaded beyond the product's load capacity.
- 4. The product is cleaned and maintained with a cleansing agent generally accepted by the industry and the instructions of the specific agent are followed.
- 5. Any abuse or misuse of, changes to, alteration of, or improper maintenance of original equipment shall void this warranty in its entirety.

If any product provided by Choice Equipment Company, Inc. shows defect in material or workmanship, CEC will, at its option, repair or replace the defective product if (1) CEC has received notice of such defects within the specified warranty period, and (2) upon CEC's request, the defective items is returned at CEC's cost to a location designated by CEC.