

Fusion

GHS 56"H Refrigerated Service Case w/ Curved Glass

Structural Concepts®

(Lengths do not include 1-1/8" end panels)

- **GHS456RLB** 48-3/4"L x 42-3/4"D x 55-1/4"H
- **GHS556RLB** 60-5/8"L x 42-3/4"D x 55-1/4"H
- **GHS656RLB** 73-1/8"L x 42-3/4"D x 55-1/4"H
- **GHS856RLB** 97-1/2"L x 42-3/4"D x 55-1/4"H
- **GHS1056RLB** 121-1/8"L x 42-3/4"D x 55-1/4"H
- **GHS1256RLB** 146-1/4"L x 42-3/4"D x 55-1/4"H

Included

- Curved lift-up front glass
- Integrated average product temperature of 40°F or less
- LED top & shelf lights
- One year parts & labor warranty
- Remote DX refrigeration
- Stainless steel rear exterior



Specify	Standard Features	Additional Options
EXTERIOR COLOR	• Powder coated (stock colors, specify RAL#)	• Laminated (non-premium) Confirm pattern/grain direction • Stainless steel
INTERIOR COLOR	• Black powder coated	• Stainless steel
LOWER FRONT PANEL COLOR	• Black powder coated	• Stainless steel
TRIM COLOR	• Black	• Silver
BASE	• Rail system for shims	
BUMPER FRONT	• 1" Boston bumper (specify color)	• 1" Stainless steel plate rail bumper
END PANELS	• None (specify per line-up)	• Cutaway w/ glass (LH / RH) • End bumper (LH / RH) • Full w/stainless steel interior (LH / RH)
SCALE STAND	• None	¹ • Scale stand w/ receptacle & CAT5 (specify location) ¹ • Scale stand w/ receptacle (specify location)
UPPER REAR	• Clear glass rear sliding doors	• Reflective glass rear sliding doors
PRICE TAG MOLDING	• None	• 1" Price tag molding (black or silver) • Universal price tag molding (clear w/ open top)
SHELVING	• 16" & 20" & 20" Solid shelving	• 16" & 18" & 20" & 20" Glass shelving • 16" & 18" & 20" & 20" Solid shelving • 16" & 20" & 20" Glass shelving
LIGHTS	• LED 3500K w/ frosted lens	• LED 4000K w/ frosted lens
ELECTRICAL CONNECT	• Electrical leads (remote)	
REFRIGERATION	• Remote DX refrigeration	• Remote w/thermostat, solenoid & TXV
SENSOR	• None	• CPC discharge air sensor (remote) • Danfoss discharge air sensor (remote)
MISCELLANEOUS		• Front glass lock • Rear door lock
ACCESSORIES		• Drain strainer

Option Notes: 1 - Separate circuit required

