

RCC SERIES FRONT & BACK COUNTERS

REFRIGERATED CURVED COUNTERS

ALL METAL CONSTRUCTION

SOLID DOORS & DRAWERS



GLASS DOORS & DRAWERS



STANDARD FEATURES

ETL approval for UL safety and NSF sanitation
Patented access system for electrical
plumbing and refrigeration
Stainless steel adjustable feet
Aisi 304 stainless steel module with BA
external finish and 2B internal stainless steel
Round corners inside the model
Ecological CFC free polyurethane foam
Stainless steel intermediate and adjustable shelf
High capacity evaporator with fan system
Digital Dixell control with safe housing
Stainless steel counter bar
Stainless steel doors
Ventilated refrigerated
Self contained
Steel frame

OPTIONS

Stainless steel sliding drawers
Glass doors
Glass sliding drawers
Stone top
Casters
Work top options:
Flat
Back splash 8"H (199mm)
Pre-arrangement for service top
Round per "Compact Round"

REFRIGERATED CURVED COUNTERS SPECIFICATIONS

CODES	MODELS	EXTERIOR LENGTHS	INTERIOR LENGTHS	DEPTHS	HEIGHT	# OF DOORS	WEIGHTS (LBS)	VOLTAGES	AMPS
BRPVF1P58H75	90° A1A	59 1/4" (1503mm)	26 3/4" (682mm)	25 3/4" (655mm)	44 1/2" (1130mm)	1	267	120	2
BRPVF1P65H75	90° A1B	59 1/4" (1503mm)	26 3/4" (682mm)	29 1/2" (750mm)	44 1/2" (1130mm)	1	308	120	2
BRPVF2P58H75	90° A2A	72 3/4" (1846mm)	40 1/4" (1025mm)	25 3/4" (655mm)	44 1/2" (1130mm)	2	305	120	3
BRPVF2P65H75	90° A2B	72 3/4" (1846mm)	40 1/4" (1025mm)	29 1/2" (750mm)	44 1/2" (1130mm)	2	308	120	3
BRPVF2P65H75	90° C1A	41 1/4" (1051mm)	54 3/4" (1390mm)	25 3/4" (655mm)	44 1/2" (1130mm)	2	310	120	3
BRPVF2P65H75	90° C1B	41 1/4" (1051mm)	54 3/4" (1390mm)	29 1/2" (750mm)	44 1/2" (1130mm)	2	318	120	3
BRPVF2P65H75	30° A3A	52 1/4" (1329mm)	39" (990mm)	25 3/4" (655mm)	44 1/2" (1130mm)	2	308	120	3
BRPVF2P65H75	30° A3B	52 1/4" (1329mm)	39" (990mm)	29 1/2" (750mm)	44 1/2" (1130mm)	2	310	120	3
BRPVF2P65H75	30° C3A	63" (1598mm)	95 1/4" (2418mm)	25 3/4" (655mm)	44 1/2" (1130mm)	2	308	120	3
BRPVF2P65H75	30° C3B	63" (1598mm)	95 1/4" (2418mm)	29 1/2" (750mm)	44 1/2" (1130mm)	2	310	120	3

A= 25 3/4" (655mm) | B= 29 1/2" (750mm)



1441 Rollins Roads, Burlingame, CA 94010
Tel: 855.885.2400 | 650.342.2400 | Fax: 650.342.7400
sales@oscartek.com | www.oscartek.com




RCC SERIES FRONT & BACK COUNTERS


REFRIGERATED CURVED COUNTERS

OPTIONAL BACK SPLASH 8"H (199mm) SHOWN


A - 25 3/4"D (655mm)
SIDE VIEW



B - 29 1/2"D (750mm)
SIDE VIEW



90° A1



90° A2




30° A3



30° C3



90° C1




90° C6




PLAN VIEWS


90° A1




90° A2




30° A3




30° C3









90° C1



90° C6



A - 25 3/4"D (655mm)



B - 29 1/2"D (750mm)

