

Product Data Sheet

TRANSFORMER DRY 1PH 2KVA 120X240V-16/32V



BUCK AND BOOST
for the Beta 900 Electric

Part Number 371014006

Technical Characteristics

Application	Buck and Boost - Primary use is that the primary and secondary can be interconnected for use as an autotransformer
Mounting Type	Wall
Primary	120 x 240VAC
Rating	2kVA
Secondary	16/32VAC
Specifications	Sealed and Resin Filled
Temperature Rise	115 Degrees C
Type	Dry
Weathershield	Not required for outdoor use
Depth	6.56 Inches
Height	9.56 Inches
Width	8.68 Inches
Approvals	cULus Listed
Enclosure Code	9A
Enclosure Material	Painted Steel
Enclosure Rating	NEMA 3R
Enclosure Type	Rainproof and Ice/Sleet proof (Indoor/Outdoor)
Insulation Temperature	180 Degrees C

Shipping and Ordering

Category	16265 -
Discount Schedule	PE2
GTIN	00785901876496
Package Quantity	1
Weight	50.73 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y
Country of Origin	MX

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

*BE&SCO equipment is solely intended for use in a commercial facility.