# **DUAL TEMP REFRIGERATOR/FREEZER**

### Model: 1RFENHD Natural Refrigerant R-290 Model

# 1-Section Extra-Wide Dual Temp Over/Under Reach-In Refrigerator/Freezer (0°F)

1RFENHD - Stainless steel front, aluminum end panels and interior 1RFENSAHD - Stainless steel exterior, aluminum interior 1RFENSSHD - Stainless steel exterior and interior



## **Options and Accessories**

(upcharge and lead times may apply)		
Stainless steel case back	Shallow depth (consult factory)	
Additional epoxy coated steel shelves	Hinged glass doors	
Chrome or stainless steel shelves	Increased refrigeration systems (consult factory)	
Heavy duty pilaster strips	Special electrical req. (consult factory)	
Pan slide assemblies	<b>Correctional Facility Options</b>	
Rehinging of doors (consult factory)	One way security screws	
Wine rack (refrigerator section)	Locking hasp (lock not included)	
Adjustable legs	Stainless steel mesh cover	
Custom laminates	Coverless hinges	
Pass-Thru (consult factory)		

Consult factory for other model configurations, options and accessories.



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Project Name:	
Model Specified:	
Location:	
Item No:	Quantity:
AIA #:	SIS #:

# **Standard Model Features**

#### **REFRIGERATION SYSTEM**

Separate, self contained, performance rated refrigeration systems

Natural, environmentally safe, high efficiency R-290 refrigerant<sup>1</sup>

Automatic, electric condensate evaporator

Freezer section: standard operating temperature is 0 to -5°F and can be adjusted to operate as low as -10°F in a 90°F ambient.

#### **CABINET ARCHITECTURE**

3" non-CFC polyurethane foam insulation

Smooth, polished chrome workflow door handles

Cam action, lift off hinges Self-closing doors

Magnetic snap in Santoprene<sup>™</sup> door gaskets

Cylinder lock in each door

Heavy duty, epoxy coated steel shelves

5" casters

### **MODEL FEATURES**

LED interior lighting Electronic controllers with digital display & hi-low alarm Off-cycle defrost (refrigerator section) Automatic electric defrost (freezer section)

<sup>1</sup> R-290 refrigerant meets all federal and state regulatory requirements.

**APPROVAL:** 

## **Model Specifications**

DIMENSIONAL DATA	
Net Capacity (cubic feet)	11/11 (311/311 cu l)
Width, Overall (inches)	28 ½ (724 mm)
Depth, Overall (inches) (including handles)	35 ¾ (899 mm)
Depth (inches) (less doors)	32 (813 mm)
Depth (inches) (doors open 90°)	58 (1473 mm)
Clear Door Width (inches)	21 7⁄8 (556 mm)
Clear Half Door Height (inches)	27 ½ (699 mm)
Height, Overall (inches) (including 5" casters)	82 ¼ (2089 mm)
Number of Half Doors	2
Number of Shelves	4
Shelf Area (square feet)	20.4 (1.9 sq m)
Tray Slide Capacity (per half section)	11
REFRIGERANT DATA	
Condensing Unit Size (H.P.)	1/5, 1/3
Capacity (BTU per hour)*	1940 / 1590
ELECTRICAL DATA	
Voltage (International)	115/60/1 (220/50/1)
Feed Wires (including ground)	3/3
Total Amps (International)	2.7 (2.9) / 5.9 (3.1)
Defrost Amps (International)	3.9 (2.2)
10 ft. Cord/Plug [attach.] (International)	Yes (No)
SHIPPING DATA	
Height - Crated (inches)	85 ½ (2172 mm)
Width - Crated (inches)	31 5⁄8 (803 mm)
Depth - Crated (inches)	42 (1067 mm)
Volume - Crated (cubic feet)	65 (1841 cu l)
Weight Std - Crated (pounds)	435 (197 kg)
Weight SS - Crated (pounds)	495 (225 kg)
* Bating @ +25°E evaporator 90°E ambient (re	frigorator)

\* Rating @ +25°F evaporator, 90°F ambient (refrigerator) \* Rating @ -15°F evaporator, 90°F ambient (freezer)

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.

**Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

> Designed and ed in the USA



Equipped with two NEMA-5-15P Plugs (varies by country)





Due to our continued efforts in developing innovative products, specifications subject to change without notice.



© Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.







**IMPORTANT NOTE:** If the cabinet is located directly against a wall and/or under a low ceiling, a <u>minimum</u> clearance of 12" is required on top and 3" on sides and rear.