

Dukers[®]
Commercial Refrigeration
Equipment



DUKERS
Quality Commercial Refrigeration



GLASS DOOR MERCHANDISER

DSM-33R

2-Door / Glass / Swing / Refrigerator



i TECHNICAL SPECIFICATIONS

Voltage/Frequency
115V/60Hz

Refrigerant
R290

Type of Defrost
Automatic

Interior Finish
White

Exterior Finish
Black

Temperature Range °F
33 ~ 40°F

Compressor Power (HP)
1/3

Nema Config.
NEMA5-15P



PRODUCT FEATURES

- The compressor is mounted in the bottom for better heat evaporation.
- Digital temperature controls with LED display for precise adjustment and automatic defrosting system.
- Temperature Range 33 ~ 40°F, with auto defrost function, which ensures optimal performance day-in and day-out.
- R290 Natural Refrigerant promotes faster cool down and efficient energy consumption.
- Interior and canopy LED light with switch on the right side to always show your products at their best
- High quality coated stainless adjustable shelves prevent peel and rust.
- Anti-fogging tempered glass door helps ensure a crystal clear view of the interior.



HIGH QUALITY & ROBUST DESIGN



Los Angeles | San Francisco | Dallas
Houston | Florida | Chicago | New Jersey

1-800-931-8628

@ info@dukersusa.com


www.DukersUSA.com

DETAILS & SPECIFICATIONS

DSM-33R

Front View

Side View



MODEL DSM-33R

Rated Voltage	115V
Rated Frequency	60Hz
Total Input Power	430W
Total Current	3.8A
Total Capacity	33.55 cu ft
Climatic Category	4-5
Protection Type	I
Design Pressure High Side	300 PSIG
Design Pressure Low Side	150 PSIG
Insulation Blowing Gas	C-Pentane
Refrigerant	R290/5.11 oz

MODEL	EXTERNAL DIMENSION WXDXH (INCHES)	PACKAGING DIMENSION WXDXH (INCHES)	PRODUCT NET WEIGHT	# OF SHELVES	40HQ CONTAINER CERT.
DSM-33R	39 3/8 x 31 7/8 x 80 3/8	40 3/8 x 32 7/8 x 82 3/8	297 lbs	10	28



Los Angeles | San Francisco | Dallas
Houston | Florida | Chicago | New Jersey

1-800-931-8628

@ info@dukersusa.com

www.DukersUSA.com