



### QUOTE DRAWING

Sign below for acceptance

X \_\_\_\_\_

Door hinge: Left \_\_\_\_\_ Right \_\_\_\_\_

Door location wall (centered): Left \_\_\_\_\_ Front \_\_\_\_\_

By signing here, you agree to our terms and conditions as outlined on [www.uscooler.com/terms](http://www.uscooler.com/terms). Panel configuration subject to U.S. Cooler final approval. A facsimile or emailed approval of this drawing CO1010FL.PA95 shall have the same force and effect as a signed original and shall, upon receipt by U.S. Cooler, be binding on both parties.

### Materials:

ExtMetal:Galvalume

IntMetal:Galvalume

Foam:Extruded 4in.

### Legend

Ceiling \_ \_ \_ \_ \_

Floor \_ \_ \_ \_ \_

Cooler: 9'-9 1/2" x 9'-9 1/2" x 7'-6"

Scale: 3/8"= 1'



## FASTCOOLER

by U.S. Cooler

401 DELAWARE ST. \* QUINCY, IL 62301

TEL 217-228-2421 \* 800-521-2665 \* FAX 217-228-2424

CUSTOMER \_\_\_\_\_

JOB# \_\_\_\_\_

P.O.# \_\_\_\_\_

DATE 04/03/2020

DRAWN C.G. 1.0

DWG. REF  
CO1010FL.PA95

APV. \_\_\_\_\_

To aid in packing, please indicate with an X the corner where installation will be starting.

Refrigeration Specifications								
Qty	Manufacturer	Model	HP	Electrical	MCA	CmpRLA	CmpLRA	Dimensions DxWxH
<b>Pre-assembled Remote Med Temp R404A Air Cooled Outdoor Condensing Unit</b>								
1	Tecumseh	ASHR9460ZNAMS1	0.75	208-230/1Phase/60Hz		5.8	59.9	26.6"x28.4"x18.5"
1	Russell	RL6A066AEAA		115/1Phase/60Hz	0.8			15.5"x27.125"x18.125"