www.norlake.com



# ADVANTEDGE™ GLASS DOOR MERCHANDISERS -FREEZERS, SWING DOOR



PROJECT:

ITEM NUMBER:

MODEL NUMBER:

.....

## SPECIFICATIONS FOR: NLFGM23HB, NLFGM48HB, NLFGM72HB

Finish: Black powder coated exterior with white interior and stainless steel floor

Insulation: Complete cabinet is foamed-in-place with polyurethane insulation.

■ Hardware: Four heavy duty shelves, adjustable in 1/2" increments, per door. Product label

strips on shelves. Heavy duty factory-installled casters. Top LED backlit panel. Two LED light strips per door for maximum product illumination. Electronic adjustable

temperature control with digital display

<u>Doors:</u> Self-closing swing doors with energy efficient triple pane glass. Standard lock for each

door. Magnetic gaskets.

■ Electrical: 115 volt, 60 Hz, 1 phase with cord and plug

<u>Refrigeration:</u> Self-contained bottom mounted, air cooled refrigeration system with coated

evaporator coil and automatic defrost. The condensate is collected and automatically evaporated from an energy efficient vaporizer. Refrigerant flow is controlled by a


capillary tube. R290 refrigerant. Temperature range: -10°F to +10°F

Approvals: ETL Sanitation and Safety listed, DOE energy compliant


### STANDARD FEATURES


- Two LED light strips per door
- LED backlit top panel
- Factory installed casters
- Magnetic door gaskets
- Self-closing doors with lock for each door
- Four heavy duty shelves with product label strips per door
- Shelves adjustable in 1/2" increments and capable of supporting 125 lbs.
- Air cooled condensing unit
- Self-contained condensate evaporator requires no plumbing
- Automatic defrost
- Electronic adjustable temp control with digital display
- ETL Sanitation and Safety Listed
- Warranties: 3 yr. parts & labor, 5 yr. compressor





SIDE - ALL MODELS






# RLFGM48HB 81" 76.4" 22.3" 26.2" TOP NLFGM72HB

### **SPECIFICATIONS**

Models	NLFGM23HB	NLFGM48HB	NLFGM72HB
Crated Weight (lbs) (kg)	342 (155)	564 (256)	820 (372)
Crated Height (in) (cm)	84.6 (215)	84.6 (215)	84.6 (215)
Crated Width (in) (cm)	28.3 (72)	55.5 (141)	82.6 (210)
Crated Depth (in) (cm)	34.8 (89)	34.8 (89)	34.8 (89)
Interior Height (in) (cm)	50.2 (128)	50.2 (128)	50.2 (128)
Interior Width (in) (cm)	22.2 (56)	49.4 (125)	76.4 (194)
Interior Depth (in) (cm)	27.6 (70)	27.6 (70)	27.6 (70)
Overall Height (in) (cm)	81.5 (207)	81.5 (207)	81.5 (207)
Overall Width (in) (cm)	27 (69)	54 (137)	81 (206)
Overall Depth (in) (cm)	32 (81)	32 (81)	32 (81)
Gross Cubage (CuFt) (L)	23.0 (651)	49.0 (1388)	72.0 (2039)
Number of Shelves	4	8	12
Shelf Area (SqFt) (Sqm)	18.9 (1.8)	43.4 (4.0)	67.9 (6.3)
Number of Casters	4	4	6
Condensing Unit Size	1/2	1	*
Refrigerant	R290	R290	R290
Electrical Characteristics	115/60/1	115/60/1	115/60/1
Cord and Plug Furnished	Yes	Yes	Yes
NEMA Plug Configuration	5-15P	5-15P	5-15P
Total Amp Draw	8.0	9.0	*

\*Consult factory.

Specifications subject to change without notice.



GRAPHIC PANEL DIMENSIONS







Revision Date: 7/19 Part Number: 161754