

PROJECT:		
ITEM #		QTY:
MODEL #		
AIA#	SIS #	

# **WORKTOP REFRIGERATOR**

### VWR46HC



**WORKTOP REFRIG** 

### **EXCLUSIVE WARRANTY**

- 7 Year Parts, Labor and Compressor
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)





#### CABINET CONSTRUCTION

- · Stainless Steel Exterior (galvanized back & bottom)
- Aluminum Interior
- · Stainless Steel 20 Gauge Door
- · 4" High, Foamed-In-Place Backsplash
- · One Piece, Snap-In Magnetic Door Gaskets
- · 6" Casters Two With Brakes
- · 8' Cord And Plug (see electrical data for details)

#### **FEATURES**

- Full Electronic Control
- · Stay-Open Door Feature For Easy Product Loading
- Heavy-Duty Spring-Loaded Cartridge Hinges
- · Low Profile Horizontal Door Handle
- · Epoxy Coated Shelves (2 per section)

#### REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- · Side Mounted Refrigeration System
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- · Epoxy Coated Evaporator Coil
- Refrigerator Capable Of Maintaining Product Temperature 36°F To 38°F



Please Verify Qualifying Units By Visiting: www.energystar.gov/cfs

#### **OPTIONS & ACCESSORIES**

- · Stainless Steel Interior
- Stainless Steel Back
- Door LocksCutting Board

- · Additional Shelves
- · Shelf Clips (set of 4)
- Door Swing Orientation (at time of order)
- · 6" Legs Or 6" Seismic Legs
- · Casters: 3", Roller Kit, Low Profile
- Correctional Package
- Remote Models\* (6" legs only) (refrigerant must be specified at time of order, see note on back on page)

3779 Champion Blvd, Winston-Salem, NC 27105 ph: (888) 845-9800 | fax: (800) 253-5168


Rev. 7/18/24 Printed in U.S.A.


APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_




## VWR46HC









We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

3" Bottom & 2" Rear clearance is required

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS	
Net Capacity (cubic ft.)	10.8	Cabinet Voltage	115/60/1	Height	44"
Width, Overall (in.)	46 1/8"	Total Amperes	3.0	Width	49"
Depth, Overall (with handle)	34"	NEMA Plug (8' cord)	5-15P	Depth	35"
Height Overall (6" casters)	39 1/2"	REFRIGERATION DATA		Crated Weight	190 lbs
Depth, Door Open 90°	55 1/4"	Condensing Unit Size, HP	1/5	*NOTE: Remote units are field wired and comes with 6" legs. Refrigerant must be specified	
Door Opening (in.)	21 1/2" × 23 3/8"	Refrigerant*	R-290		
No. Of Doors/Shelves	1/2	Capacity (BTU/HR) (100°F/20°F)	1350		
		Heat Rejection (BTU/HR)	2025	at time of order.	
		Charge (lbs/grams/ounces)	0.243 / 110 / 3.89		

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Rev. 7/18/24 Printed in U.S.A.

