

# **Rack/Tray Carts**



### **RACK DOLLY**

- Stainless dolly of 14 gauge stainless steel.
   Model No. 337-2404
- ◆ Aluminum dolly of .125 aluminum Model No. 311-1215
- ◆ 20-1/4"L x 20-1/4"W x 6"H
- All models are engineered to safely transport and store any load of 20" x 20" racks filled with cups and glasses.
- ♦ Four 4" swivel-type casters

## TRAY CART

## Model No. 337-3470

- ◆ 16"L x 21"W x 31"H
- ◆ Stainless steel shelf and handle
- ◆ Four 4" swivel-type casters
- ♦ 31-1/2" high; 6-1/2" to top of shelf

## **RACK CART**

# Model No. 337-3475

- ◆ 21"L x 21"W x 31"H
- ◆ Stainless steel shelf and handle
- ◆ Four 4" swivel-type casters
- ◆ 31-1/2" high; 6-1/2" to top of shelf

IOB	ITEM #	QTY#	

## **MODEL NUMBER**

RACK DOLLY RACK CART

□ 337-2404
□ 337-3475

**311-1215** 

TRAY CART CABINET DOLLY

**□** 337-3470 **□** 2-2128

## **CABINET DOLLY**

## Model No. 2-2128

- ◆ Aluminum dolly of .125 aluminum
- ◆ Four 4" swivel-type casters
- ◆ Dolly for 912 (Stackable Cabinet; Spec J-5)

### **OPTIONS**

- □ B Corner bumper
   (Not available on 2-2128)
   (337-3470 & 337-3475 receive two corner bumpers on side opposite handle and two rotating bumpers on handle side)
- □ PB Perimeter bumper (Available for 337-2404 & 311-1215 only)
- ☐ WB Two locking casters
- ☐ Y4 Polyurethane 4" casters (set of 4)
- ☐ Y5 Polyurethane 5" casters (set of 4)
- ☐ CP Correctional Package (Casters welded on unit)

MODEL#	DESCRIPTION	SHELF SIZE	HT. FROM FLOOR TO TOP OF HANDLE	GAUGE OF SHELVES	NO. OF SHELVES	SHELF HT. FROM FLOOR	OVERALL HEIGHT	LOAD CAP. (LBS)	SHIP WT.
337-3470	Stainless Steel Tray Cart (with Tubular handle)	21-1/2" X 16-1/2"	31"	18 ga. SS	1	10"	N/A	500	24
337-3475	Stainless Steel Rack Cart (with Tubular handle)	21-1/2" X 21-1/2"	31"	18 ga. SS	1	10"	N/A	500	24
337-2404	Stainless Steel Rack Dolly	20-1/2" Sq.	N/A	14 ga. SS	1	N/A	5 7/8"	500	14
311-1215	Aluminum Rack Dolly	20-1/2" x 21-1/2"	N/A	.125 Al	1	N/A	5 7/8"	500	14
2-2128	Aluminum Cabinet Dolly	21-3/4"W X 28-3/8"D	N/A	.125 Al	1	N/A	7 3/4"	500	25

LIMITED WARRANTY: PIPER PRODUCTS warrants to the original purchaser parts and labor for a period of twelve (12) months from the date of purchase. See manufacturer's complete warranty for details.

It is our policy to build equipment which is design certified by companies that have been accredited at the Federal Level by the Occupational Safety and Health Agency (OSHA) and ANSI as a National Recognized Testing Laboratory. These companies include CSA International, Underwriters Laboratories, and the National Sanitation Foundation. However, a continuing program of product improvement makes it necessary to submit new models to the agencies as they are developed. Consequently, all models may not bear the appropriate labels at all times.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Information is not for design purposes.

BUILT TO LAST www.piperonline.net

SPEC H-3
300 S. 84th Avenue

Wausau, WI 54401 Phone: 800-544-3057 Fax: 715-842-3125