

INSTALLATION INSTRUCTIONS BUILT-IN NARROW DRAWER WARMERS MODELS RWN-26 (T)


ELECTRICAL

MODEL	VOLTS	WATTS	AMPS	PHASE	FIELD WIRING GAUGE	TEMP. RATING
RWN-26	120	900	7.5	SINGLE	14 AWB Cu	90°C
RWN-26	208	676	3.3	SINGLE	14 AWB Cu	90°C
RWN-26	240	900	3.8	SINGLE	14 AWB Cu	90°C


ALL MODELS WITH A 'T' SUFFIX HAVE THE SAME ELECTRICAL SPECIFICATIONS AS THE STANDARD VERSIONS.

INCHES
(MM)

CUTOUT DETAILS



PRODUCT DIMENSIONS



CLEARANCES

THERE ARE NO CLEARANCE REQUIREMENTS FOR THIS UNIT.

INSTALLATION INSTRUCTIONS

INSTALLER MUST MEET CONDITIONS OF ACCEPTABILITY OUTLINED BELOW UPON INSTALLATION:

TO FABRICATE:

1. Layout front panel cutout dimensions and cutout hole in counter front panel.
2. Position attaching flange (supplied) in hole cutout to determine screw hole location. Drill holes using #34 drill.
3. Attach flange to front panel using #6 screws provided.
4. Fabricate rails and rear support in locations shown.

TO INSTALL:

1. For ease of installation, remove drawers from unit.
2. Slide unit through front panel opening until rear of unit engages rear support.
3. Remove upper control knob and upper control panel.
4. Install #8-32 speednuts on attaching flange, secure attaching flange to front panel, then secure unit to attaching flange using #8-32 flathead screws provided.
5. Connect service leads to the unit including ground wire.
6. Replace control panel and control knob.
7. Replace drawer.

