MOBILE BARS

For Beverage Service Using Post-Mix/Bag-in-Box

"BBC" SERIES

Increase beverage sales with a portable bar designed for post-mix / bag-in-box service - built to serve as the toughest bar in town

- Designed to be outfitted with your post-mix or bag-in-box dispensing system drink concentrates are chilled and mixed as they dispense
- Available in a variety of styles to fit into any space:
 - Weather-All Stainless Steel Throughout
 - · Professional Laminate Exterior
 - · Executive Maple Wood Exterior
 - Architectural Mahogany Wood Exterior
 Wood and laminate styles come in a variety of stain and color options (see back)
- Made for mobile applications All BBC series bars are constructed with a stainless steel tubular welded base frame designed to absorb shock during transport
- 4 Keeps six drink mix flavor circuits cold with a sealed in cold plate and 50lb capacity insulated ice bin with drain and sliding stainless steel cover (8' bars come with two (2) ice bins)
- Easy to clean the sanitary stainless steel work areas and interior make clean up quick and easy
- 6 Accessories include stainless steel condiment holder and removable speed rail with towel ring
- Matching back bar and ice carts are available in each style FWE offers: Weather-all, Professional, Executive, and Architectural

*Two Year Limited Warranty





Designed for Bag-in-Box



Made for Mobile Applications




50lb Ice Bin with Drain



Removable Bottle Speed Rail

SPECIFICATIONS

MOBILE BARS



Stainless and Laminate Models are NSF Approved

	Stailless and Laminate Models are NSF Approved										
			Factory for G CLASS SHIP								
	MODEL NUMBER	HIGH "H"	DEEP [A] "D"	WIDE "W"	WORKING AREA HEIGHT	STORAGE AREA DIMS (IN)	CASTER SIZE	WT . LBS. (KG)			
Stainless Steel	SBBC-5	45.75" (1162)	29.25" (743)	59.5" (1511)	35.5" (902)	30W x 28.5H x 23D	5"	420 (191)			
	SBBC-6	45.75" (1162)	29.25" (743)	72" (1829)	35.5" (902)	43.25W x 28.5H x 23D	5"	510 (232)			
	SBBC-8	45.75" (1162)	29.25" (743)	95" (2413)	35.5" (902)	40.5W x 28.5H x 23D	5"	635 (289)			
Laminate	BBC-5	45.75" (1162)	29.25" (743)	59.5" (1511)	35.5" (902)	30W x 28.5H x 23D	5"	425 (193)			
	BBC-6	45.75" (1162)	29.25" (743)	72" (1829)	35.5" (902)	43.25W x 28.5H x 23D	5"	510 (232)			
	BBC-8	45.75" (1162)	29.25" (743)	95" (2413)	35.5" (902)	40.5W x 28.5H x 23D	5"	740 (336)			

		Consult Factory for SHIPPING CLASS						
	MODEL NUMBER	HIGH "H"	DEEP [A] "D"	,	WORKING AREA HEIGHT	STORAGE AREA DIMS (IN)	CASTER SIZE	SHIP WT . LBS. (KG)
Maple Wood	ES-BBC-5	45.75" (1162)	29.25" (743)	59.5" (1511)	35.5" (902)	30W x 28.5H x 23D	5"	450 (205)
	ES-BBC-6	45.75" (1162)	29.25" (743)	72" (1829)	35.5" (902)	43.25W x 28.5H x 23D	5"	530 (241)
	ES-BBC-8	45.75" (1162)	29.25" (743)	95" (2413)	35.5" (902)	40.5W x 28.5H x 23D	5"	605 (275)
Mahogany Wood	AS-BBC-5	45.75" (1162)	32.5" (826)	60.5" (1537)	35.5" (902)	30W x 28.5H x 23D	5"	570 (259)
	AS-BBC-6	45.75" (1162)	32.5" (826)	73.25" (1861)	35.5" (902)	43.25W x 28.5H x 23D	5"	660 (300)
	(B) AS-BBC-8	45.75" (1162)	32.5" (826)	96" (2439)	35.5" (902)	40.25W x 28.5H x 23D	5"	868 (394)

[A] The depth dimensions include standard removable 4.5" deep speed rail.

[B] 8 foot models furnished with 2 ice bins.

*Adding a full bumper will add 1.5" to the width and .5" to depth.



Scan QR code for our full wood and laminate selection sheet

CONSTRUCTION. Heliarc welded, single unit construction shall consist of welded stainless steel base frame of heavy gauge I" square stainless steel tubing with extra 10 gauge stainless steel caster corner plate reinforcements. Full length, heavy gauge stainless steel angles reinforce front corners of body on inside with high impact edging on outside corners. Work surface shall be constructed of 20 gauge stainless steel. Interior of body shall be lined with 22 gauge stainless steel, bonded to cabinet walls and bottom storage area. Seams shall overlap for greater durability and moisture resistance. Work and splash areas shall be polished stainless steel with easy-to-clean coved corners. Front edge shall have raised marine nosing to contain spills. Black laminate top with bull-nose rounded corners

FINISH MATERIALS & TOP.

SBBC Series: Shall be stainless steel, heliarc welded: ground and polished exterior and stainless steel bar top.

BBC Series: Front and side panels shall be high-pressure, dual-side counter-balanced laminate .75" thick finish. Laminate selections are available. Full length, heavy gauge stainless steel angles reinforce front corners of body on inside, with high impact edging on outside corners. Black laminate top with bull-nose rounded corners

ES-BBC Series: Classic raised solid maple wood panels. All wood surfaces finished with polymer coating to deter scratching and gouging. Constructed with reinforced joints for additional strength and durability. Black solid surface top. AS-BBC Series: Classic raised solid mahogany wood panels, fluted columns, crown molding. Black laminate bar top with an oversized

mahogany wood "Chicago Arm" surround.

Solid brass kick plate provided in front and sides of unit. All wood surfaces finished with polymer coating to deter scratching and gouging. Constructed with reinforced joints for additional strength and durability.

CASTERS. Maintenance free polyurethane tire casters in a configuration of two (2) rigid and two (2) swivel with brake. Eight (8) foot models are equipped with six (6) casters: two (2) rigid casters and four (4) swivel with brake. Casters shall have a reinforced yoke mounted to 10 gauge caster plate. The caster mounting plate shall be secured to a 10 gauge stainless steel reinforcing stress plate via welded in place stainless steel studs. The reinforcing stress plates shall be welded to the heavy gauge tubular base frame.

STORAGE AREA. On all models, the bottom storage area shall be stainless steel lined.

BAR ACCESSORIES. Standard equipment shall include 4.25" deep, heavy gauge stainless steel full length bottle speed rail; removable without tools. Towel ring shall be mounted to working side. Stainless steel condiment holder provided.

INSULATED ICE BIN WITH DRAIN, Ice bin with drain shall be one-piece stainless steel with coved corners: 19.75" x 12.75" x 10.5" deep. Ice bin shall have enclosed foam insulation with drain and line fittings with shut-off drain valve. 6 circuit sealed-in cold plate shall be compatible for use with Bag-in-Box systems. 8 foot models shall have two (2) ice bins with drains and circuits. Ice bin shall have a capacity of 50lbs of ice, and be provided with a stainless steel sliding cover.

INSTALLATION. Unit should not be installed in an area where adverse environmental

DOORS Locking doors

CASTERS (BBC & SBBC only)

Larger casters **BUMPERS** (BBC & SBBC only) Corner bumpers

Full perimeter bumper Vertical stainless steel corner guards **EXTRAS**

Locking bottle speed rail Stainless steel bar gutters Protective storage cover Custom laminate or stain Custom tops Graphic wrap (SBBC only) Built-in electric hand sink Double-hung speed rail Bag-in-box dispensing system

Post-mix dispensing system

conditions are present.





