





Stainless Solid (No Flange)



Key Features

- $\bullet\,$ Makes crescent shaped cubes approx. $^{1}\!/^{2}''$ W x $^{3}\!/^{4}''$ H x 2 $^{1}\!/^{4}''$ L
- Produces up to 25 lb of ice per day
- Stores 25 lb of ice
- On / off switch
- · White interior

- Stainless steel handle (1/8" diameter)
- Field reversible door is shipped right-hand hinged
- Built-in or freestanding
- No drain required


Model Details


Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
UMCR015-SS01A	115 / 60	Field Reversible	Stainless Solid	73 lb (33 kg)


Accessories

Model	Description	Finish	Shipping Weight
ULAWATERHOOKUP	Braided water supply line kit	N/A	2 lb

Side Top **Front**








Specifications

Model	MCR015
Amps: Running	2.5 amps
Amps: Max Start Up	18 amps
Control Type	On/Off Switch
Defrost Type	Manual
Dimensions: Product Depth	20 ½" (511 mm)
Dimensions: Product Height	27 ½" (699 mm)
Dimensions: Product Width	14 1/8" (378 mm)
ENERGY STAR	N/A
Ice Production Per Day	25 lb (11,3 kg)
Product Weight: Max	68 lb (30,8 kg)
Refrigerant Type	R600A



Back

Cabinet Cut-Out

Filler Panel (Not Provided by U-Line) – May Be Added Above or Below Unit to Enclose for a Built-In Look See Electrical Specifications for Power Supply Typical Counter Height 34-1/4" Preferred location for electrical outlet 18-1/2" (870 mm) to 35-1/8" (470 mm) is in adjacent cabinet. (892 mm) Cut-Out **®** Height 25-1/16" (637 mm) - 14-3/16"-(360 mm)

Warranty

- 1 Year (parts & labor) / 5 year sealed system (parts)
- Additional 1 Year (parts & labor) warranty at no cost with product registration

See complete warranty for details





- No additional clearance is needed for ventilation
- Do not obstruct front grille air flow



