HR24C-G 08/16/23 Item # 13596

WxDxH 23.4" x 24.7" x 31.5"

## HR24C-G





















Dimensions / Capacity	One Section HR24C-G
Interior Storage Capacity (CF) (AHAM)	3.87 ft <sup>3</sup>
Overall Width x Depth (with handle)	23.4" x 26.5"
Height	31.5"
Depth with Door Open at 90°	46.7"
Adjustable Shelves	3
Shelf Dimensions (W x D)	(1) 18.5" x 17", (2) 18.5 x 12"
Crated Weight	115 lbs.
Crated Shipping Dimensions (WxDxH)	26.8" x 24" x 36.6"
Electrical / Refrigeration	One Section HR24C-G
Voltage	115/60/1
HACR Breaker	15.0 Amps
<b>Electrical Connection</b> (NEMA)	5-15P 🛈
Voltage Range	115-127
Ambient Temp. Range	45° to 100°F
Control Setpoint Range	34° to 52°F
Amperage	1.1
Energy Consumption (kWh/day) @ASHRAE	0.64
Heat Rejection (BTU/Hr.) @NSF	648
Approx. Nominal Compres. BTU/HR (HP)	501 (1/8HP)
Refrigerant (charge amount, oz.)	R600a (0.9 oz.)

#### **Options/Accessories**

☐ Wine rack kit

#### Warranty

3 Year - parts and Labor on entire machine.

Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

Item #:	
Project:	
Qty:	
AIA#:	

# **Features**


- Stainless steel interior and exterior front, sides and top
- UL approved for outdoor use
- ► Interior LED lighting
- Stainless steel exterior door with aluminum interior comes standard with locks
- Field reversible door with full length tubular handle
- · Magnetic door gasket is easily removable for cleaning
- Environmentally friendly insulation
- Electronic controls with LED Temperature Display and Audio/Visual Alarm
- · High and low temperature alarms as well as "Door Open" alarm
- · Automatic time-initiated defrost
- (3) Epoxy coated shelves standard
- 9 ft. cord and 5-15P NEMA plug
- Three year parts and labor warranty


If GFCI is required, a GFCI breaker MUST be used in lieu of GFCI receptacle Hoshizaki reserves the right to change specifications without notice.





FRONT VIEW SIDE VIEW inch [mm]





### **PLAN VIEW**

