



natural refrigerant.

Design

• True's commitment to using the highest quality materials and energy efficient refrigeration systems provides the user with colder product temperatures and lower utility costs.

FEATURES

- Take advantage of the install flexibility, convenience, and efficiency of this self-contained case. Fit TRM's through doorways, move the case into location, install the compact sealed condensing systems and plug it in. No refrigeration connections or technicians needed for install.
- Available in 2,3, and 4 door models, the TRM's are ideal for multi-door case lineups, end cap placements, and general refrigeration storage applications.
- The entire cabinet structure is built using high-density, polyurethane insulation that has zero ozone depletion potential.
- Refrigeration redundancy architecture helps prevent product loss.

Refrigeration System

- With the R290 Natural Refrigeration system, TRM is exempt from changing state and federal regulations.
- Environmentally friendly R290 Natural Refrigerant system.
- Self-contained factory-charged and sealed refrigeration system.
- The True Dynamic Refrigeration Response System allows for quick product pull down where and when cooling demand is needed.
- DOE and Energy Star approved.

Accessories

• Peg-bar shelf for organized display of hanging products

Welcoming

a sustainable approach to merchandising

Introducing the next generation of full-sized grocery merchandiser, True's Retail Merchandiser (TRM) is an advanced self-contained cabinet built for large storage capacity and exceptional product display.



The TRM refrigeration system is charged and sealed at the factory using R290 refrigeration, a natural, environmentally friendly future proof refrigerant.

Electrical

Unit completely pre-wired at factory and ready for final connection to a 208-240V-1PH-60Hz, cord and plug set included. 208-240/60

NEMA-L6-20P

Innovation

- Reverse condensing fan motor (RCU) technology helps prevent condenser blockage.
- Patented True Level leveling systems for a quick install.
- Plug-and-play electrical system for seamless installation (No refrigeration tech or electrician needed).
- High Efficiency Variable Speed Compressor Technology

Doors

- Self closing doors with stay open feature.
- "Low-E" triple pane thermal insulated glass door.
- Viewable glass height of 70" for maximum product display.
- Magnetic door gasket of one piece construction, removable without tools for ease of cleaning.

LED Lighting

• 4000k color temperature LED interior lighting, provides brilliant lighting throughout the cabinet.

Shelving

• Total of 15 (5 per door) adjustable, solid white powder coated cantilever shelves 30W" x 25D".

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 • Fax (636)272-2408 • Toll Free (800)325-6152 Intl Fax# (001)636-272-7546 • Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • truemfg.com



PHYSICAL DATA		PLAN VIEWS
LED Color Temperature	4000k	Cabinet illustrated includes the (NN) end
# Of Refrigeration Decks	2	
Usable Capacity Cubic Ft	116.2	FRONT VIEW SIDE VIEW
Internal Dimensions	92 5⁄8″ x 31″ x 68 1⁄8″	
Cabinet Dimensions	97 ¹⁵ ⁄16″ x 39 7⁄8″ x 102″	36 21/32"
Door Type	Glass	18 31/32" [482mm]
Crated Weight (lbs)	1318	
Interior Finish	White Aluminum	
External Finish	Black Aluminum	
Shelf Type Design	Cantilever	
# Of Full Shelves	15	
Full Shelf Dimensions	30 ³ /16″W x 25″D	[239 mini]
Castors Legs/ Levelers	Leg Levelers	78 27/32 [2002mm] DOOR
Stay Open Door Feature	Yes	
ELECTRICAL & EN		80 1/2" [1730mm] 1 [2045mm]
Daily Energy Use (Kwh/Day)	27.3	
Energy Star Certified	Yes	
Condenser Type	Air Cooled	
Rejected Heat (Btu/h)	6454	
Horse Power (Per Deck)	2 ½ (2 x 1¼)	
Total Amps	13.8	
Cord Length	10'	
Electrical Plug	NEMA-L6-20P	
REFRIGERATIC		
Refrigerant Charge (per deck)	10.5oz (5.25 x 2)	
Refrigerant	R290	
Min. Temperature	-10°	
Max. Temperature	6°	
END PANEL OV CONFIGURATION	ERALL COMBINED	97 15/16" [2486mm]
TRM3-NN	98	• TRM3L-NN
TRM3-YN	96 ³ ⁄4	TRM NOMENCLATURE
TRM3-NY	97 1/8	TRAINOPENCEATORE
TRM3-YY	96 3 ⁄4	Sections/Doors Side of Door
PANELS		Tarrita 2 3 4 Interior Finish Hinge LED Light Temp.
N = 2 ½" (End panel) Y= 1 ½" (In-line panel)		Family WHT White L Left 4000k TRM True Retail Merchandiser BLK Black R Right
Y= 1 ½" (In-Iin	e panel)	
END PANEL	CONFIGURATION	EXAMPLE TRM3L-BLK-WHT-1BLKLL-YN-4
MULTI UI	NIT LINE UP	1 STAND ALONE Temperature
		L Freezer Door End Panel Thickness M Refrigerator Cabinet Exterior Version
NY	YY YN	NN BLK Black WHT White Door Color
		YIN YIN
		BC_202953_1.23
		2.1_2CC2.2.2_3 (
	NS ROUNDED UP TO T	
NEAREST WI	HOLE MILLIMETER	refrigerant.
SPECIFICATIONS WITHO	SUBJECT TO CHANGE	PARTS + LABOR COMPRESSOR
		truemfg.com in 🖸 🞯 WARRANTY