# REACH-IN FREEZER (0°F)

## Model: 1FNPTHD

Natural Refrigerant R-290 Model

# 1-Section Pass-Thru Freezer with Half Doors

**1FNPT-HD** - Stainless steel front, aluminum end panels and interior **1FNSA-PT-HD** - Stainless steel exterior, aluminum interior **1FNSS-PT-HD** - Stainless steel exterior and interior




### **Options and Accessories**

#### (upcharge and lead times may apply)

Additional epoxy coated steel shelves	Hinged glass doors (consult factory)	
Chrome or stainless steel shelves	Special electrical req. (consult factory)	
Rehinging of doors (consult factory)	Correctional Facility Options	
Pan slide assemblies	One way security screws	
Full door	• Locking hasp (lock not included)	
Adjustable legs	Stainless steel mesh cover	
Custom laminates	Coverless hinges	

Consult factory for other model configurations, options and accessories.



## **Standard Model Features**

#### **REFRIGERATION SYSTEM**

Self contained, performance rated<br/>"plug" refrigeration systemNatural, environmentally safe,<br/>high efficiency R-290 refrigerant1Refrigeration system is readily accessible on<br/>top of cabinet, separate from the "food zone"Automatic, hot gas condensate evaporatorExpansion valve system

#### **CABINET ARCHITECTURE**

3" non-CFC polyurethane foam insulation	
Smooth, polished chrome workflow door handles	
Cam action, lift off hinges	
Self-closing doors	
Magnetic snap in Santoprene™ door gaskets	
Cylinder lock in each door	
Heavy duty, epoxy coated steel shelves	
Heavy duty pilaster strips	
5" casters	

#### **MODEL FEATURES**

#### LED interior lighting

Electronic controller with digital display & hi-low alarm
Top and side air distribution ducts
Automatic electric defrost
Cabinet upper side panels and refrigeration "plug" system can be removed and reinstalled at job site

<sup>1</sup> R-290 refrigerant meets all federal and state regulatory requirements.



**Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

APPROVAL:

## **Model Specifications**

DIMENSIONAL DATA	
Net Capacity (cubic feet)	21 (595 cu l)
Width, Overall (inches)	26 (660 mm)
Depth, Overall (inches) (including handles)	38 ¾ (984 mm)
Depth (inches) (less doors)	32 (813 mm)
Depth (inches) (doors open 90°)	79 (2007 mm)
Clear Door Width (inches)	19 ¾ (492 mm)
Clear Half Door Height (inches)	27 ½ (699 mm)
Height, Overall (inches) (including 5" casters)	82 ¼ (2089 mm)
Number of Doors	4
Number of Shelves	3
Shelf Area (square feet)	20.4 (1.9 sq m)
Tray Slide Capacity (per half section)	11
REFRIGERANT DATA	
Condensing Unit Size (H.P.)	1/2
Capacity (BTU per hour)*	1590
ELECTRICAL DATA	
Voltage (International)	115/60/1 (220/50/1)
Feed Wires (including ground)	3
Total Amps (International)	6.9 (4.2)
Defrost Amps (International)	4.3 (2.2)
10 ft. Cord/Plug [attached] (International)	Yes (No)
SHIPPING DATA	
Height - Crated (inches)	85 ½ (2172 mm)
Width - Crated (inches)	31 5⁄8 (803 mm)
Depth - Crated (inches)	42 (1067 mm)
Volume - Crated (cubic feet)	65 (1841 cu l)
Weight Std - Crated (pounds)	355 (165 kg)
Weight SS - Crated (pounds)	415 (188 kg)
* Dating @ 15% avanagatag 00% ambient	

\* Rating @ -15°F evaporator, 90°F ambient Figures in parentheses reflect metric equivalents rounded to the nearest

whole unit.

Toll-Free: 800-523-7138 Phone: 215-244-1400

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Proudly Designed and

Fax: 215-244-9579

• 

Equipped with one NEMA-5-15P Plug (varies by country)





Due to our continued efforts in developing innovative products, specifications subject to change without notice.



© Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

## **Model Plan Views**





**IMPORTANT NOTE:** If the cabinet is located under a low ceiling, a <u>minimum clearance of 12</u>" is required on top and 3" on sides.