

72 " Restaurant Series RANGE

▪ R 72 2ST - 72 B ▪ R 72 2CO - 72 B

72 " Restaurant Series RANGE



Model R 72 2ST - 72 B

100% manufactured from raw materials providing the highest quality and durability

STANDARD FEATURES

RANGE

- 2-year parts and labor warranty
- Lifetime Warranty Non-Clog Burners
- 7 " stainless steel belly rail
- 14 gauge fully welded interlocking frame
- 22.5 " Flue riser standard with shelf
- Standing pilot for open top burners
- Heavy duty 12 " x 12 " removable cast iron grates
- Stainless steel front and sides
- Metal Black insulated Knobs
- Heavy duty single over shelf
- 6 " Adjustable legs

OVEN BASE

- 35,000 BTU/h oven with snap action thermostat from 175°F to 550°F (79.4°C to 287.7°C) and 100% safety shut off
- 26 ½ " Standard bakery depth on all ovens
- Spark ignition for oven bases
- Enamelled oven cavity (top, bottom and side)

- Heavy duty oven wired rack – 3/8 " diameter
- Standard oven has 4 shelf positions and 3 racks standard

CO- Convection Oven (Optional)

- **Dynamic Airflow Technology (DAT)** Patented convection oven with a low-profile fan, 26 ½ " depth, and a high-pressure balanced air flow design
- 5 shelf positions and 4 racks standard
- Convection oven has an on/off switch and high/low fan speed
- Only Convection oven base that fits a full-size sheet pan on all models

OPTIONS & ACCESSORIES

- Modular belly rail accessory for 1/6 pans
- Cutting Board
- (4)6" swivel casters with front locking brakes
- Oven Rack
- Quick disconnect (3/4 Flex hose quick disconnect 4' long)
- Stub Back FlueRiser

SPECIFICATIONS

RANGE


- 32,000 BTU/h Burners, providing maximum control and best heat distribution in the industry
- ¾ " NPT rear gas connect and pressure regulator for both natural gas and propane
- Manifold pressure is 4 " W.C. (Natural Gas) or 10 "W.C. (Propane Gas)
- Each burner is controlled by a gas valve for independent control of flame. One standing pilot services each burner
- 6 " stainless steel, adjustable legs.

OVEN

- 35,000 BTU/h burners
- One standing pilot services each burner



▪ R 72 2ST - 72 B ▪ R 72 2CO - 72 B



Model	Exterior Product Dimensions & Weight				Shipping Crate Dimensions & Weight			
	Width	Depth	Height	Weight	Width	Depth	Height	Weight
R 72 2ST - 72 B	72 " (1,830 mm)	34 ¼ " (871 mm)	60 " (1,524 mm)	884 lb (401 kg)	75 19/32 " (1,920 mm)	50 1/32 " (1,271 mm)	44 3/32 " (1,120mm)	1060 lb (481 kg)
R 72 2CO - 72 B	72 " (1,830 mm)	42 ¼ " (1,073 mm)	60 " (1,524 mm)	1069 lb (485 kg)	75 19/32 " (1,920 mm)	57 3/32 " (1,450 mm)	44 3/32 " (1,120mm)	1246 lb (565 kg)

Model	Oven Interior		
	Width	Depth	Height
R 72 2ST - 72 B	2 of 26 ½ " (673.1 mm)	2 of 26 ½ " (673.1 mm)	2 of 14 " (355.6 mm)
R 72 2CO - 72 B	2 of 26 ½ " (673.1 mm)	2 of 26 ½ " (673.1 mm)	2 of 14 " (355.6 mm)

UTILITY INFORMATION

GAS SUPPLY

Model	Burners (Range)	Gas (BTU/h)		Burners (Oven)	Gas (BTU/h)		Manifold Pressure	
		Natural	Propane		Natural	Propane	Natural Gas	Propane gas
All models	12	384,000	360,000	2 *	70,000	66,000	4 " W.C.	10 " W.C.

* 1 per oven

- ¾ " NPT rear Gas inlet.
- Specify elevation, if over 2000 ft
- LP conversion kit included

ELECTRICAL

- Convection Oven with ¼ HP, 115 V, 60 Hz, 3.30/3.70 A, 1 phase motor , 1,125 and 1,725 rpm supplied with 6.5 ' (2000 mm) cord

CLEARANCES REQUIREMENTS

- Provide side and rear clearance 0 " (0 mm) from non-combustible surfaces. 8 " (203.2 mm) – rear and 6 " (152.4 mm) sides, clearance from combustible surfaces.

MISCELLANEOUS

- Install under vented hood
- Check local codes for fire, installation and sanitary regulations
- Intended for commercial use only. Not for household use

