

# WORKTOP REFRIGERATOR

MODEL: UCT 44 01

# PRO-KOLD

## Product features

- Stainless steel top with 3" backsplash for controlled food prep
- Digital control for easy read-out and temperature adjustment
- Adjustable, interior shelf
- Casters included for maintaining cleanliness under and around unit
- Easy to clean stainless steel floor
- Forced air refrigeration system to promote even cooling throughout unit
- Injected with polyurethane of high density foam with cyclopentane



## Available Color

STAINLESS  
STEEL

## Accessories

- Additional shelves

## Product highlights



Fluorescent Lighting



Intelligent temperature control



Easy access to condensing unit

## Certifications



## Warranty

- 2 year parts and labor
- Additional 3 year compressor coverage


Residential: Assumes on liability for parts or labor coverage for component failure, factory defect or any other damages for units installed in non-commercial foodservice or residential applications.

## PRODUCT SPECIFICATIONS


### MODEL: UCT 44 01

## Plan view


Front view



Top view



Side view



## Technical data

### Dimensions

External dimensions	W: 44" D: 35" H: 40"
Internal dimensions	W: 25.23" D: 26.33" H: 26.32"
Net volume	10.1 ft3 (286 Lts.)
Net weight	213 Lbs.
Gross weight	316.58 Lbs.
Packaging dimensions	W: 51" D: 42" H: 46"

### Performance data

Refrigerant charge	6.70 oz
Energy consumption	5.85 kwh/24h
Condenser	Ventilation forced
Evaporator	Ventilation forced
Evaporation temperature	19.94°F
Expansion method	Capilar
Thawing method	By time

### Construction

Exterior material	Stainless steel
Interior material	Stainless steel floor
Number of shelves	1
Shelf material	Pre-painted steel
Door type	Stainless steel door
Door quantity	1

\* W= Width, D= Depth, H= Height

### Electrical data

Power supply	110v/ 60 Hz
Amps	5.3 A
Length of cord	118" (3000mm)
Lighting	Fluorescent
Plug type	NEMA-5-15P
Controller	Digital
Compressor power	1/4 HP

### Cooling

Temperature range	36°F to 41°F (Exhibition)
Refrigerant	R134a
Defrosting	Automatic
Temperature controller	Digital
Optimum temperature range	36°F to 41°F (Storage)

### Logistic data

Trailer Loads	54 fit on a 53' trailer
Unit weight with packaging	316.58 Lbs.
Dimensions with packaging	W: 51" D: 42" H: 46"