



DIMENSIONS & SHIPPING WEIGHT

37 5/8" W X 54 1/8" D X 41 3/4" H
(956 mm X 1375 mm X 1061 mm)
840 lb (381 kg)

INTERIOR DIMENSIONS

43 5/8" W X 53 3/8" D X 36 3/4" H
(1108 mm X 1356 mm X 985 mm)
840 lb (381 kg)

CAPACITY

16 Half Size Sheet Pans (13" x 18" - 330mm x 457mm)
Shelf Spacing: 4" (102 mm)
(Requires use of wire shelves to hold half size sheet pans)

8 Full Size Sheet Pans (18" x 26" - 457 mm x 660 mm)
Shelf Spacing: 4" (102 mm)

ELECTRICAL SYSTEM

1 Phase (Ground Wire not Included):

- ☐ 208-240V - 50 A - 10.8 kW - 50/60 Hz - 2 Wires (JA8X)
- ☐ 208V - 80 A - 10.8 kW - 50/60 Hz - 2 Wires (JA8XR)
- ☐ 240V - 70 A - 10.8 kW - 50/60 Hz - 2 Wires (JA8XR)
- ☐ 208-240V - 6 A - 1.5 kW - 50/60 Hz - 2 Wires (JA8XG)
- ☐ 120V - 8.5 A - 1 kW - 60 Hz - 2 Wires (JA8XG)

3 Phase (Ground Wire not Included):

- ☐ 208-240V - 30 A - 10.8 kW - 50/60 Hz - 3 Wires (JA8X)
- ☐ 208V - 47 A - 17 kW - 50/60 Hz - 3 Wires (JA8XR)
- ☐ 240V - 43 A - 17 kW - 50/60 Hz - 3 Wires (JA8XR)
- ☐ 480V - 20 A - 17 kW - 50/60 Hz - 3 Wires (JA8XR)
- ☐ 480V - 12.5 A - 10.8 kW - 50/60 Hz - 3 Wires (JA8X)
- ☐ 208-240V - 5 A - 1.5 kW - 50/60 Hz - 3 Wires (JA8XG)

Job:

Item No.

Jet Air Oven—New Design

MODEL: JA8X (Electric)
JA8XG (Gas)
JA8XR (Retherm)

FEATURES & BENEFITS

- Intuitive Programmable Touchscreen Control
- Door switch cutoff for fan blower
- Stainless steel construction
- Unique Pulse & Shot Steam
- Dependent Doors for Single Hand Operation
- Advanced Moisture Evacuation System
- Jet Air Exclusive Patented Reversing Fan System
- Available in Electric (JA8X, JA8XR) or Gas (JA8XG)
- Available with Rethermalization (JA8XR only)
- Two Year Parts and One Year Labor Warranty

OPTIONS & ACCESSORIES

- ☐ Water Filter (PLF240)
- ☐ Equipment Stand (JA8B)
- ☐ Nickel Plated Pizza Shelf (GRPIZ8)
- ☐ Gas Connection Kit (4' [1200 mm] flexible hose, ball valve, & securing device) (GAH600) (for JA8XG only)
- ☐ Manual Backup Thermostat Control

WATER CONNECTION

Water: 1/4"

GAS CONNECTION (JA8XG Only)

Water: 1/2"

FINISH

Stainless Steel

STANDARD PRODUCT WARRANTY



One Year Labor & Two Year Parts

MINIMUM CLEARANCES

1" (25 mm) Side & Back
4" (102 mm) Bottom
12" (305 mm) Top

SHORT SPECIFICATION

Jet Air Oven, Electric, Programmable Touchscreen Control, Dependent Doors with Single Hand Operation, Stainless Steel Construction Interior & Exterior, Advanced Moisture Evacuation System, Available in Electric (JA8X - 10.8 kW) - Gas (JA8XG) - Retherm (JA8XR - 17 kW), 1/4" Water Connection for Steam, ETL & NSF Listed



PRODUCTION CAPACITY

Product (Fresh State)	Bake Time	Bake Temp (°F)	Bake Temp (°C)	Quantity Produced
9" Cakes	18 - 22 minute	350	177	144
9" Pies	30 - 35 minute	375	190	120
Bagels (16 per pan)	15 minute	350	177	512
Dinner Rolls (16 per pan)	15 - 18 minute	350	177	512
Sub Rolls 12" (10 per pan)	15 - 18 minute	350	177	320
French Baguettes (5 per pan)	20 - 25 minute	350	177	120
Croissants (15 per pan)	12 - 15 minute	350	177	480
Muffins (15 per pan)	18 - 22 minute	325	163	360
Muffins (24 per pan)	18 - 22 minute	325	163	576
9" Quiches	30 - 35 minute	350	177	120
Cookies (18 per pan)	8 - 10 minute	300	149	864
Danish (15 per pan)	12 - 15 minute	350	177	480
Biscuits (15 per pan)	8 - 10 minute	350	177	600
Bread (4 strapped pan)	30 - 35 minute	375	190	64
Cinnamon Rolls (8/half pans)	15 - 18 minute	325	163	512
Brownies (16 1/2oz box)	12 minute	350	177	40