



DROP-IN PLACE ICE CHEST
Standard Depth With and Without Cold Plate



COMPONENT



JOB	
AREA	
ITEM NO.	
MODEL NO.	

MODELS	
Non-Cold Plate	Cold Plate
DI17IC	
DI18IC	
DI24IC	DI24IC10
DI30IC	DI30IC10
DI36IC	DI36IC10

MODEL NUMBERS - DI17IC, DI18IC, DI24IC, DI24IC10, DI30IC, DI30IC10, DI36IC, DI36IC10

KEY PRODUCT FEATURES AND BENEFITS

- All stainless for durable easy to clean surfaces
- Fully insulated to reduce ice melt in warm climates
- Eco-friendly foam insulation is efficient and has zero impact on global warming or ozone depletion

Quick Features:

- Fully insulated with highly efficient eco-friendly polyurethane foam
- Built with stainless steel to maximize the lifespan
- Boldly innovative cold plate design increases thermo efficiency to instantly chill your soft drink to the right temperature
- Highly efficient cold plates instantly chill your soft drinks to the correct temperature
- Available with or without a cold plate to suit your bartender's needs



DROP-IN PLACE ICE CHEST
Standard Depth With and Without Cold Plate

MODEL NUMBERS - DI171C, DI181C, DI241C, DI241C10, DI301C, DI301C10, DI361C, DI361C10

MODEL NOS.						
MODEL TYPE:	Non-Cold Plate Models	DI171C	DI181C	DI241C	DI301C	DI361C
	Cold Plate Models	NA	NA	DI241C10	DI301C10	DI361C10
DIMENSIONS:	Outside (Length x Width)	19" x 26"	20" x 19-1/4"	26" x 19-1/4"	32" x 19-1/4"	38" x 19-1/4"
	Inside (Length x Width)	15" x 21-3/4"	15-3/4" x 15"	21-3/4" x 15"	27-3/4" x 15"	33-3/4" x 15"
	Cut-Out Size, Inches	17-7/8" x 24-5/8"	18-5/8" x 17-7/8"	24-5/8" x 17-7/8"	30-5/8" x 17-7/8"	36-5/8" x 17-7/8"
	Ice Capacity, lb/kg	80 (36.3)	55 (36.3)	80 (36.3)	100 (45.4)	120 (54.4)
	Ship Weight With Cold Plate lb/kg	N/A	N/A	80 (36.3)	86 (39)	92 (41.7)
	Ship Weight Without Cold Plate lb/kg	28 (12.7)	28 (12.7)	33 (15)	39 (17.7)	45 (20.4)
MATERIALS	Top	Stainless steel				
	Front & Sides	Galvanized steel				
	Back & Bottom	Galvanized steel				
	Covers	Stainless steel, two-piece, included with all Drop In Ice Chests				
	Insulation	Eco-friendly foamed-in-place polyurethane				
MECHANICALS	Plumbing	Drain connection- 1-1/2" NPS male				
	Cold Plate	Cast aluminum plate concealed under ice chest liner. Cold plate has 2 full-length circuits and 8 half-length circuits. Connections - 5/16" O.D. stainless steel tubing with swaged end to accept standard 1/4" I.D. beverage tubing				
OPERATING SPECIFICATIONS	Cold Plate	Each full circuit will deliver four 6 oz. drinks per minute at 40° continuously, or 40 oz. every three minutes in a single draw (flow rate 2 oz./sec, 75° product)				

DI171C

(Sets in place with narrow edge to the front)

